

INTERIOR USL-T81U
Cooler Lights




Interior


Damp Location


AC


5 Year Warranty





OVERVIEW

These tubes are suitable for use in freezer and refrigerated displays, walk-in coolers, and vending machines. Available with G13 pins or a flat flange for mounting.

FEATURES

- 2-8 feet long
- G13 pins or mounting flange
- Suitable for damp locations
- Ideal for freezers and coolers
- 240° or 180° beam angles



ORDERING INFORMATION

EXAMPLE PN: USL-T81U-4-18W-LV-50K-180D-C-G

USL-T81U	SIZE / POWER*	VOLTAGE	CCT	BEAM ANGLE	LENS	END CAP
	2-9W 2 FEET, 9 WATTS	LV 100-277V	30K 3000K	180D 180°	C CLEAR	F FLANGE
	3-9W 3 FEET, 9 WATTS		40K 4000K	240D 240°	F FROSTED	G G13
	3-14W 3 FEET, 14 WATTS		50K 5000K			
	4-15W 4 FEET, 15 WATTS					
	4-18W 4 FEET, 18 WATTS					
	4-22W 4 FEET, 22 WATTS					
	5-18W 5 FEET, 18 WATTS					
	5-22W 5 FEET, 22 WATTS					
	5-26W 5 FEET, 26 WATTS					
	6-22W 6 FEET, 22 WATTS					
	6-26W 6 FEET, 26 WATTS					
	6-30W 6 FEET, 30 WATTS					
	8-30W 8 FEET, 30 WATTS					
	8-36W 8 FEET, 36 WATTS					

*Note: only 4/5/6 ft are DLC-listed

SPECIFICATIONS

MODEL	OPERATION VOLTAGE	OPERATING TEMPERATURE	RATED LIFESPAN	CCT	CRI	EFFICACY
USL-T81U	100-277V AC	-4°F – 140°F -20°C – 60°C	50,000 H OURS	3000K, 4000K, 5000K	80+	115-130 lm/W

MODEL	POWER (W)	LENGTH (ft)	LUMENS (lm)	EFFICACY (lm/W)
USL-T81U-2-9W	9	2	1,035	115
USL-T81U-3-9W	9	3	1,125	125
USL-T81U-3-14W	14	3	1,680	120
USL-T81U-4-15W	15	4	1,950	130
USL-T81U-4-18W	18	4	2,250	125
USL-T81U-4-22W	22	4	2,640	120
USL-T81U-5-18W	18	5	2,340	130
USL-T81U-5-22W	22	5	2,750	125
USL-T81U-5-26W	26	5	3,120	120
USL-T81U-6-22W	22	6	2,860	130
USL-T81U-6-26W	26	6	3,250	125
USL-T81U-6-30W	30	6	3,600	120
USL-T81U-8-30W	30	8	3,900	130
USL-T81U-8-36W	36	8	4,500	125

