

INTERIOR USL-UC2L

CCT Selectable Under Cabinet Light



PROJECT	TYPE	DATE
---------	------	------

Interior
 Damp Location
 Dimmable
 AC
 Down Light
 Color Select
 5 Year Warranty
 ETL

OVERVIEW

This under cabinet light is available in lengths from 8 inches to 32 inches. It features a micro-switch to select the color temperature. The slim 1" profile keeps the fixture out of sight. The lens extends the length of the fixture to evenly distribute the light. The module design and connection options gives flexibility in installation.



FEATURES

- Color-section switch
- Low profile of 1 inch
- 5-100% dimming
- PF > 0.9
- 106° beam angle
- Aluminum body with polycarbonate lens



ORDERING INFORMATION

EXAMPLE PN: USL-UC2L-24-14W-CS-W

USL-UC2L	SIZE / POWER	CCT	FINISH
8-6W	8 INCHES, 6 WATTS	CS COLOR SELECTABLE 2700K/3000K/4000K	W WHITE
16-10W	16 INCHES, 10 WATTS		
24-14W	24 INCHES, 14 WATTS		
32-16W	32 INCHES, 16 WATTS		

*Note: Color-selectable option is a switch to select 2700K, 3000K, or 4000K.

ACCESSORIES

USL-UC2L-ACC	ACCESSORY
--------------	-----------

- PWR** 5-foot power cord
CBL 6-inch connection cable
CNT Male to female connector



POWER CABLE CONNECTION CABLE MALE-FEMALE CONNECTOR

CCT Selectable Under Cabinet Light



SPECIFICATIONS

MODEL	OPERATION VOLTAGE	RATED LIFESPAN	CCT	CRI	EFFICACY
USL-UC2L	120V	50,000 HOURS	2700K, 3000K, 4000K	90+	75-90W

MODEL	POWER (W)	LUMENS (lm) ±10%	CURRENT	EQUIVALENT	EFFICACY (lm/W)
USL-UC2L-8-6W	6	450	0.05	35W	75
USL-UC2L-16-10W	10	900	0.08	59W	90
USL-UC2L-24-14W	14	1,050	0.12	65W	75
USL-UC2L-32-16W	16	1,200	0.13	75W	75

DIMENSIONS

MODEL	L LENGTH	W WIDTH	H HEIGHT	WEIGHT
8-6W	7.9 in 200 mm	3.7 in 93 mm	1 in 25 mm	0.53 lb
16-10W	15.9 in 405 mm			1.04 lb
24-14W	24 in 610 mm			1.51 lb
32-16W	32 in 813 mm			2.14 lb

