

INTERIOR USL-EME2V Edge-lit Exit Sign



PROJECT	TYPE	DATE
---------	------	------



Interior



Damp Location



Non-Dimming



AC



Battery Option



5 Year



OVERVIEW

These exit signs are edge-lit. They can be recessed mounted or they can be surface mounted--either back or flag style. Installation hardware includes adhesive chevron arrows and templates for their installation. The 4.8V NiCd batter provides a minimum of 90 minutes illumination.



FEATURES

- Meets UL924, NFPA 101 Life Safety Code, NEC & OSHA codes
- User decides chevron arrow configuration
- 6" letters
- 90-minute NiCd battery
- For use with 120V or 277V AC
- Mounting hardware is included



SURFACE MOUNT



RECESSED MOUNT



ORDERING INFORMATION

EXAMPLE PN: USL-EME2V-SC-G

USL-EME2V	MOUNTING	FACES	TEXT COLOR
SM	SURFACE MOUNT	SC	SINGLE-SIDED, CLEAR
RM	RECESSED MOUNT	DS	DOUBLE-SIDED, SILVER
		G	GREEN TEXT
		R	RED TEXT

INTERIOR USL-EME2V Edge-lit Exit Sign



SPECIFICATIONS

MODEL	OPERATION VOLTAGE	OPERATING TEMPERATURE	CCT	CRI	EFFICACY
USL-EME2V	120 OR 277	32°F – 122°F 0°C – 50°C	NA	NA	NA

TECHNICAL & ELECTRICAL PARAMETERS

BATTERY INDICATION LIGHT	Green = normal Red = check battery
BATTERY RECHARGE TIME	24 hours
POWER @ 120V	3.6 W
CURRENT DRAW @ 120V	0.03 A
POWER @ 277V	4.0 W
CURRENT DRAW @ 277V	0.02A
WEIGHT OF SURFACE-MOUNT	3.75 lbs
WEIGHT OF RECESSED-MOUNT	7.5 lbs

DIMENSIONS

