

ARCHITECTURAL USL-B23Z

Barrett Suspended Pendant



PROJECT		TYPE		DATE	
---------	--	------	--	------	--

Architectural
 Interior
 Damp Location
 Dimmable
 DMX
 AC
 Down Light
 Up/Down
 5 Year Warranty
 ETL
 ENERGY STAR

OVERVIEW

This suspended pendant is built with an aluminum profile and die-cast end caps that hide the screws (if using a non-ring model). 0-10V dimming supports dimming to 10% or 1%. The powder coat finish can be done in custom RAL colors.

FEATURES

- 1-10V dimming (10%-100% or 1%-100%)
- DMX and DALI controls available
- THD < 10%
- Pendant or surface mount
- IP20



ORDERING INFORMATION

EXAMPLE PN: USL-B23Z-32U-112W-30K-10VA-G

USL-B23Z	SIZE / POWER	CCT	DIMMING	FINISH
32D-75W	32" RING, DOWN LIGHT, 75W	30K 3000K	0 NON-DIMMING	G GRAY
40D-90W	40" RING, DOWN LIGHT, 90W	40K 4000K	10VA 0-10V (10%)	B BLACK
48D-108W	48" RING, DOWN LIGHT, 108W	50K 5000K	10VB 0-10V (1%)	W WHITE
32U-112W	32" RING, UP/DOWN LIGHT, 112W		DALI DALI	### CUSTOM RAL
40U-135W	40" RING, UP/DOWN LIGHT, 135W		DMX DMX	
48U-162W	48" RING, UP/DOWN LIGHT, 162W			

ACCESSORIES

USL-B23Z-ACC	ACCESSORY
SP-KIT	Suspension mount kit
SM-KIT	Surface mount kit

ARCHITECTURAL USL-B23Z Barrett Suspended Pendant



SPECIFICATIONS

MODEL	OPERATION VOLTAGE	RATED LIFESPAN	CCT	CRI	EFFICACY
USL-B23Z	100-270V	50,000 HOURS	3000K, 4000K, 5000K	80+	80-89 lm/W

MODEL	POWER (W)	LIGHT DISTRIBUTION	LUMENS (lm) ±10%	EFFICACY (lm/W)
USL-B23Z-32D-75W	75	DOWN	6,000	80
USL-B23Z-40D-90W	90		8,000	89
USL-B23Z-48D-108W	108		9,000	83
USL-B23Z-32U-112W	112	1/3 UP 2/3 DOWN	10,000	89
USL-B23Z-40U-135W	135		11,000	81
USL-B23Z-48U-162W	162		14,000	86

DIMENSIONS

MODEL	DIAMETER
USL-B23Z-32	31.49 in 800 mm
USL-B23Z-40	39.37 in 1000 mm
USL-B23Z-48	47.24 in 1200 mm

PROFILE VIEW

