

INTERIOR USL-SDL2L Slim Down Light



Interior



Dimmable



Wet
Location



5
Year
Warranty



OVERVIEW

This slim down light is a flush mount LED fixture that can be mounted junction boxes and replaces standard 4" and 6" recessed housings. It is composed of a polycarbonate lens with an aluminum ring.

FEATURES

- Dimmable with most TRIAC and ELV dimmers
- Aluminum ring with powder coat finish
- Polycarbonate lens
- Title 24 compliant
- Replaces 4" and 6" recessed lighting



ORDERING INFORMATION

EXAMPLE PN: USL-SDL2L-6-15W-30K-W

USL-SDL2L	SIZE / POWER	CCT	FINISH
	4-12W 4 INCHES, 12 WATTS	27K 2700K	W WHITE
	6-15W 6 INCHES, 15 WATTS	30K 3000K	
		40K 4000K	
		50K 5000K	

INTERIOR USL-SDL2L Slim Down Light



SPECIFICATIONS

MODEL	OPERATION VOLTAGE	RATED LIFESPAN	CCT	CRI	EFFICACY
USL-SDL2L	120V	50,000 HOURS	2700K, 3000K, 4000K, 5000K	90+	52-55 lm/W

MODEL	REPLACES	POWER (W)	LUMENS (lm) $\pm 10\%$	INCANDESCENT EQUIVALENT	EFFICACY (lm/W)
USL-SDL2L-4-12W	4"	11.5	600	65W	52
USL-SDL2L-6-15W	6"	16.5	900	75W	55

DIMENSIONS

MODEL	D DIAMETER	H HEIGHT	WEIGHT
USL-SDL2L-4-12W	6.26 in	1.18 in	0.15 lb
	158 mm	28 mm	0.07 kg
USL-SDL2L-6-15W	7.36 in	1.18 in	0.46 lb
	187 mm	28 mm	0.21 kg

