

INTERIOR USL-IU3J

Indirect Linear Light



PROJECT		TYPE		DATE	
---------	--	------	--	------	--

- Interior
- Dry Location
- Dimmable
- AC
- Up/Down
- Battery Option
- 5 Year Warranty

OVERVIEW

This fixture is compatible with track lighting; can be surface mounted; or can be pendant mounted via chain, cord, or rod. It can work on normal mains and automatically switch to emergency supply in the event of a power failure. This is done by self-contained batteries or by using two independent emergency lighting circuits in the trunking.



FEATURES

- Indirect lighting
- 10% uplight, 90% downlight
- 5, 8, or 12-core through-wiring
- UGR < 19
- Emergency options
- Multiple mounting options
- Daisy chain (100m) at 220V



ORDERING INFORMATION

EXAMPLE PN: USL-IU3J-4-60W-40K-WD-5-W-V-0

USL-IU3J	SIZE / POWER	CCT	BEAM ANGLE	TRACK WIRE	FINISH	DIMMING	EMERGENCY POWER
	4-30W 4 FT, 30W	27K 2700K	WD WIDE BEAM, DOWN ONLY	5 5-WIRE	W WHITE	V 0-10V	0 NONE
	4-45W 4 FT, 45W	30K 3000K		8 8-WIRE	B BLACK	D DALI	11 6W RAIL, 1800 mAh BATTERY
	4-60W 4 FT, 60W	35K 3500K	WU WIDE BEAM, UP/DOWN	12 12-WIRE	S SILVER		12 6W RAIL, 3600 mAh BATTERY
	8-60W 8 FT, 60W	40K 4000K					21 12W RAIL, 1800 mAh BATTERY
	8-90W 8 FT, 90W	50K 5000K	ND NARROW BEAM, DOWN ONLY				22 12W RAIL, 3600 mAh BATTERY
	8-120W 8 FT, 120W	57K 5700K	NU NARROW BEAM, UP/DOWN				
		65K 6500K					

ACCESSORIES

USL-IU3J-ACC	ACCESSORY
L	L-shaped corner connector
T	T-shaped 3-way connector
X	X-shaped 4-way connector
EC	End cap (2 pcs per row required)
FD	Feed-in connector/feed-in box (1 set per row)
SCD	Suspension cord
SCN	Suspension chain
SM	Surface-mount installation kit

INTERIOR USL-IU3J

Indirect Linear Light



SPECIFICATIONS

MODEL	OPERATION VOLTAGE	OPERATING TEMPERATURE	RATED LIFESPAN	CCT	CRI	EFFICACY
USL-IU3J	100-277V AC	-14°F - 140°F -25°C - 60°C	50,000 HOURS	2700K-6500K	80+	145 lm/W

MODEL	LENGTH	POWER (W)	LUMENS (lm) ±10%	EFFICACY (lm/W)
USL-IU3J-4-30W	4 ft 1200 mm	30	4,350	145
USL-IU3J-4-45W		45	6,500	145
USL-IU3J-4-60W		60	8,700	145
USL-IU3J-8-60W	8 ft 2400 mm	60	8,700	145
USL-IU3J-8-90W		90	13,050	145
USL-IU3J-8-120W		120	17,400	145

DIMENSIONS

MODEL	L LENGTH	W WIDTH	H HEIGHT
4-FOOT	47.3 in 1201.7 mm	9.3 in 236 mm	7.2 in 183.2 mm
8-FOOT	94.6 in 2403.4 mm		

