

EXTERIOR USL-WPF1A

Full Cutoff Wall Pack



OVERVIEW

This full cut-off wall pack was designed and built with high performance, efficiency and cost effectiveness in mind. The LEDs are housed in a sealed compartment separate from the drivers to keep them cool. A bubble level is built in and a gasket is included to ensure proper and simple installation. The unit is lightweight while being extremely durable. Ideal applications include building exteriors, entryways and walkways, parking lots and security lighting.



FEATURES

- Die-cast aluminum body
- Dark Sky compliant
- Type 3 polycarbonate optical lens contains UV stabilizers
- Easy to install; contractor friendly
- Built-in level
- Quick disconnect and hinges
- Optional photocell
- IP65

ORDERING INFORMATION

EXAMPLE PN: USL-WPF1A-70W-LV-40K-D-0

USL-WPF1A	-	POWER*	-	VOLTAGE*	-	CCT	-	FINISH	-	PHOTOCELL*
		45W 45 WATTS		12V 120 VOLTS		40K 4000K		B BLACK		0 NO PHOTOCELL
		70W 70 WATTS		27V 277 VOLTS		50K 5000K		D DARK BRONZE		P0 120-277V
		90W 90 WATTS		LV 120-277 VOLTS				W WHITE		P1 120V
		135W 135 WATTS								P2 277V
		50W 50 WATTS		34V 347V						
		75W 75 WATTS								
		95W 95 WATTS								
		145W 145 WATTS								

*Note: 120V and 277V specification only required when getting photocell option, otherwise, specify 120-277 volts.
45/70/90/135W available with 120-277 volts, 50/75/95/145W available with 347 volts.

EXTERIOR USL-WPF1A

Full Cutoff Wall Pack



SPECIFICATIONS

MODEL	OPERATION VOLTAGE	AMBIENT OPERATING TEMP	CCT	CRI	EFFICACY
USL-WPF1A	120-277V 347V	-40°C – 50°C -40°C – 122°F	4000K, 5000K	80+	94-109 lm/W

MODEL	VOLTAGE (V)	POWER (W)	CCT	LUMENS (lm)	EFFICACY (lm/W)	REPLACEMENT
USL-WPF1A-45W-LV-40K	120-277V	45	4000K	4,800	107	175-250W HID
USL-WPF1A-45W-LV-50K	120-277V	45	5000K	4,900	109	175-250W HID
USL-WPF1A-50W-34V-40K	347V	50	4000K	4,800	96	175-250W HID
USL-WPF1A-50W-34V-50K	347V	50	5000K	5,000	100	175-250W HID
USL-WPF1A-70W-LV-40K	120-277V	70	4000K	7,300	104	250-400W HID
USL-WPF1A-70W-LV-50K	120-277V	70	5000K	7,350	105	250-400W HID
USL-WPF1A-75W-34V-40K	347V	75	4000K	7,400	99	250-400W HID
USL-WPF1A-75W-34V-50K	347V	75	5000K	7,500	100	250-400W HID
USL-WPF1A-90W-LV-40K	120-277V	90	4000K	9,300	103	320-400W HID
USL-WPF1A-95W-LV-50K	120-277V	90	5000K	9,500	106	320-400W HID
USL-WPF1A-95W-34V-40K	347V	95	4000K	9,300	98	320-400W HID
USL-WPF1A-90W-34V-50K	347V	95	5000K	9,500	100	320-400W HID
USL-WPF1A-135W-LV-40K	120-277V	135	4000K	13,600	101	400W+ HID
USL-WPF1A-135W-LV-50K	120-277V	135	5000K	14,000	104	400W+ HID
USL-WPF1A-145W-34V-40K	347V	145	4000K	13,600	94	400W+ HID
USL-WPF1A-145W-34V-50K	347V	145	5000K	14,000	97	400W+ HID

DIMENSIONS

	45W - 75W	90W - 145W	DIMENSIONAL DRAWINGS		
D DEPTH	8.78 in 223 mm	10.8 in 274.57 mm			
H HEIGHT	9.25 in 235 mm	9.75 in 247.65 mm			
W WIDTH	14.21 in 361 mm	18.09 in 459.68 mm			