

# INTERIOR USL-TRI2E Tri-Proof Strip Light



## OVERVIEW

This linear fixture is water-proof, dust-proof, and pressure-proof. It is extremely durable and suitable in humid environments. Up to 600W can be connected together.

## FEATURES

- IP66
- IK10 impact protection rating
- PF>0.95
- THD<20%
- 120° beam angle
- Rugged design



## ORDERING INFORMATION

EXAMPLE PN: USL-TRI2E-600-30W-40K

USL-TRI2E	SIZE / POWER	CCT		
	<b>600-30W</b>	2 FT, 30 WATTS	<b>30K</b>	3000K
	<b>900-40W</b>	3 FT, 40 WATTS	<b>40K</b>	4000K
	<b>1200-40W</b>	4 FT, 40 WATTS	<b>50K</b>	5000K
	<b>1200-60W</b>	4 FT, 60 WATTS	<b>60K</b>	6000K
	<b>1500-80W</b>	5 FT, 80 WATTS		
	<b>1800-90W</b>	6 FT, 90 WATTS		
	<b>2400-90W</b>	8 FT, 90 WATTS		
	<b>2400-120W</b>	8 FT, 120 WATTS		

## ACCESSORIES

USL-TRI2E-ACC	ACCESSORY
<b>SUSPKIT</b>	Suspension kit, 2 pieces, 1m standard length
<b>JBXKIT</b>	Junction box mounting kit

# INTERIOR USL-TRI2E Tri-Proof Strip Light



## SPECIFICATIONS

MODEL	OPERATION VOLTAGE	OPERATING TEMPERATURE	RATED LIFESPAN	CCT	CRI	EFFICACY
USL-TRI2E	100-277V AC	-22°F – 122°F -30°C – 50°C	50,000 HOURS	3000K, 4000K 5000K, 6000K	80+	110 lm/W

MODEL	POWER (W)	LUMENS (lm)	EFFICACY (lm/W)
USL-TRI2E-600-30W	30	3,300	110
USL-TRI2E-900-40W	40	4,400	110
USL-TRI2E-1200-40W	40	4,400	110
USL-TRI2E-1500-80W	80	8,800	110
USL-TRI2E-1800-90W	90	9,900	110
USL-TRI2E-2400-90W	90	9,900	110

## DIMENSIONS

MODEL	L	W	H
<b>USL-TRI2E-600-30W</b>	24.7 in 628 mm	3.5 in 90 mm	2.4 in 62 mm
<b>USL-TRI2E-900-40W</b>	35.4 in 900 mm	3.5 in 90 mm	2.4 in 62 mm
<b>USL-TRI2E-1200-40W</b>	47.2 in 1200 mm	3.5 in 90 mm	2.4 in 62 mm
<b>USL-TRI2E-1500-80W</b>	59.1 in 1500 mm	3.5 in 90 mm	2.4 in 62 mm
<b>USL-TRI2E-1800-90W</b>	70.5 in 1790 mm	3.5 in 90 mm	2.4 in 62 mm
<b>USL-TRI2E-2400-90W</b>	94.5 in 2400 mm	3.5 in 90 mm	2.4 in 62 mm

