

INTERIOR USL-EMS2V Stencil-Face Exit Sign



PROJECT	TYPE	DATE
---------	------	------

Interior
 Damp Location
 Non-Dimming
 AC
 Battery Option
 5 Year Warranty
 UL

OVERVIEW

These exit signs mimic the standard aesthetic of traditional emergency exit signage, but are illuminated with LED. Available in green and red text. It can be mounted to the wall or ceiling from the top, back, or sides.



FEATURES

- Meets UL924, NFPA 101 Life Safety Code, NEC & OSHA codes
- Traditional aesthetic
- 1.2V 90-minute NiCd battery
- Red or green text, 6" letters
- User decides chevron arrow configuration
- Canopy for top or side mounting
- Knockouts on back for wall mounting



ORDERING INFORMATION

EXAMPLE PN: USL-EMS2V-GRN-SS-W

USL-EMS2V	TEXT COLOR	FACES	FINISH
	RED RED	SS SINGLE-SIDED	W WHITE
	GREEN GREEN	DS DOUBLE-SIDED	

INTERIOR USL-EMS2V Stencil-Face Exit Sign



SPECIFICATIONS

MODEL	OPERATION VOLTAGE	OPERATING TEMPERATURE	CCT	CRI	EFFICACY
USL-EMS2V	120/277	-4°F – 122°F -20°C – 50°C	NA	NA	NA

TECHNICAL & ELECTRICAL PARAMETERS

BATTERY INDICATION LIGHT	Green = normal Red = check battery
BATTERY VOLTAGE	1.2V
BATTERY RECHARGE TIME	24 hours
POWER @ 120V	1W
CURRENT DRAW @ 120V	0.9A
POWER @ 277V	1W
CURRENT DRAW @ 277V	.09A
WEIGHT OF FIXTURE	2.5 lbs

DIMENSIONS

