


EXTERIOR USL-WLIJ

Up Down RGB Wall Washer



OVERVIEW

Providing color both as up light and down light, the Up Down RGB wall washer can make any building stand out. This product adopts the latest LED technology with high lumen efficiency combined with an IP65 rating. The product provides excellent light distribution and can add a pop of color to a business.

FEATURES

- IP65
- Life span of over 50,000 hours
- 5-year warranty
- Aluminum alloy and tempered glass for durability



ORDERING INFORMATION

EXAMPLE PN: USL-WLIJ-12W-UD-BLU-30D

USL-WLIJ	POWER*	LIGHT ORIENTATION*	CCT	VOLTAGE	BEAM ANGLE
6W	6 WATTS	DD DOWN	RGB RGB	LV 90-265V AC	10D 10°
9W	9 WATTS		27K 2700-3500K		12VD 12V DC
12W	12 WATTS		40K 4000-5000K	24VD 24V DC	30D 30°
18W	18 WATTS	UD UP/DOWN	50K 5000-6500K		45D 45°
12W	12 WATTS		RED RED		60D 60°
18W	18 WATTS		GRN GREEN		90D 90°
24W	24 WATTS		BLU BLUE		
36W	36 WATTS		YEL YELLOW		

*Note: Down version available in 6/9/12/18W. Up/down model available in 12/18/24/36W.

EXTERIOR USL-WLIJ

Up Down RGB Wall Washer



SPECIFICATIONS

MODEL	OPERATION VOLTAGE	AMBIENT OPERATING TEMP	RATED LIFESPAN	CCT	CRI	EFFICACY
USL-WLIJ	90-265V AC 12/24V DC	-40°F – 122°F -40°C – 50°C	50,000 HOURS	2700-3500K 4000-5000K 5000-6500K	80+	100-111 lm/W

MODEL	LIGHT ORIENTATION	POWER PER LIGHT (W)	TOTAL POWER (W)	LUMENS (lm) ±10%			EFFICACY (lm/W)
				27K	40K	50K	
USL-WLIJ-6W-DD	DOWN OR UP	6	6	600	630	660	100-110
USL-WLIJ-9W-DD		9	9	900	945	990	100-110
USL-WLIJ-12W-DD		12	12	1,200	1,260	1,320	100-110
USL-WLIJ-18W-DD		18	18	1,800	1,890	1,980	100-110
USL-WLIJ-12W-UD	UP/DOWN	6	12	1,200	1,250	1,300	100-108
USL-WLIJ-18W-UD		9	18	1,800	1,900	2,000	100-111
USL-WLIJ-24W-UD		12	24	2,400	2,500	2,600	100-108
USL-WLIJ-36W-UD		18	36	3,600	3,800	4,000	100-111

DIMENSIONS

DOWN MODEL	D DIAMETER	H HEIGHT
USL-WLIJ-6W-DD	3.45 in 90 mm	6.3 in 160 mm
USL-WLIJ-9W-DD	4.33 in 110 mm	7.87 in 200 mm
USL-WLIJ-12W-DD	5.71 in 145 mm	7.87 in 200 mm
USL-WLIJ-18W-DD	6.3 in 160 mm	9.84 in 250 mm

UP/DOWN MODEL	D DIAMETER	H HEIGHT
USL-WLIJ-12W-UD	3.54 in 90 mm	10.24 in 260 mm
USL-WLIJ-18W-UD	4.25 in 108 mm	11.81 in 300 mm
USL-WLIJ-24W-UD	5.7 in 145 mm	11.81 in 300 mm
USL-WLIJ-36W-UD	6.3 in 160 mm	16.54 in 420 mm

