

# INTERIOR USL-SLED2V Wraparound Strip Light



PROJECT	TYPE	DATE
---------	------	------



## OVERVIEW

This linear strip fixture is suitable for a wide range of applications such as storage and utility areas, cove lighting, display cases, and task or general lighting. It can be surface mounted, pendant mounted, or attached to t-bars in a grid ceiling.


## FEATURES

- IP44, PF > 0.9, THD < 15%
- 110° beam angle
- Surface mount, pendant mount, or mount to t-bars in grid ceiling
- Connect fixtures together (up to 275W)
- Optional emergency battery (internal and external option)
- Internal or external motion sensor
- Aluminum body, polycarbonate lens, aluminum PCB



EXTERNAL MOTION SENSOR

INTERNAL MOTION SENSOR



## ORDERING INFORMATION

EXAMPLE PN: USL-SLED2V-4-24W-LV-45K-10V-MS

USL-SLED2V	SIZE / POWER <sup>[1]</sup>	VOLTAGE	CCT <sup>[2]</sup>	DIMMING	OPTIONS
<b>2-10W</b>	2 FT, 10W	<b>LV</b> 120-277V	<b>30K</b> 3000K	<b>10V</b> 0-10V	<b>0</b> NONE
<b>2-15W</b>	2 FT, 15W (NOT DLC)	<b>HV</b> 347/480V	<b>35K</b> 3500K		<b>MS</b> MOTION SENSOR
<b>2-24W</b>	2 FT, 24W		<b>40K</b> 4000K		<b>EMS</b> MOTION SENSOR WITH EMERGENCY BATTERY
<b>4-24W</b>	4 FT, 24W		<b>45K</b> 4500K		
<b>4-40W</b>	4 FT, 40W		<b>50K</b> 5000K		
<b>8-40W</b>	8 FT, 40W				
<b>8-64W</b>	8 FT, 64W				

[1] Note: 2 foot 15W is not DLC listed

[2] Note: 3000K is standard

## ACCESSORIES

USL-SLED2V-ACC	ACCESSORY
<b>SMNT</b>	Surface-mount kit (comes standard)
<b>PMNT</b>	Pendant mounting kit
<b>TMNT</b>	T-bar mounting kit
<b>EM-INT</b>	Internal mounted emergency driver
<b>EM-EXT</b>	External mounted emergency driver
<b>MS-INT</b>	Internal mounted motion sensor
<b>MS-EXT</b>	External mounted motion sensor



SUSPENSION KIT

SURFACE MOUNT KIT

# INTERIOR USL-SLED2V Wraparound Strip Light



## SPECIFICATIONS

MODEL	OPERATION VOLTAGE	OPERATING TEMPERATURE	RATED LIFESPAN	CCT	CRI	EFFICACY
USL-SLED2V	120-277, 347, 480V	-4°F – 104°F -20°C – 40°C	50,000 HOURS	3000K, 3500K, 4000K, 4500K, 5000K	80+	124-141 lm/W

MODEL	LENGTH (ft)	POWER (W)	LUMENS (lm) ±10%					EFFICACY (lm/W)
			3000K	3500K	4000K	4500K	5000K	
USL-SLED2V-2-10W	2 ft	10W	1,290	1,310	1,320	1,330	1,340	129-134
USL-SLED2V-2-15W		15W	1,950	1,965	1,980	1,995	2,010	130-134
USL-SLED2V-2-24W		24W	2,980	3,145	3,170	3,190	3,215	124-134
USL-SLED2V-4-24W	4 ft	24W	3,145	3,210	3,265	3,325	3,380	131-141
USL-SLED2V-4-40W			40W	5,235	5,235	5,265	5,295	5,325
USL-SLED2V-8-40W	8 ft	40W	5,315	5,345	5,370	5,370	5,425	133-136
USL-SLED2V-8-64W			64W	8,395	8,460	8,525	8,590	8,655

## DIMENSIONS

MODEL	L LENGTH	W WIDTH	H HEIGHT
USL-SLED2V-2	23.6 in 600 mm	3.23 in 82 mm	3.23 in 82 mm
USL-SLED2V-4	48 in 1220 mm		
USL-SLED2V-8	96 in 2440 mm		

