

INTERIOR USL-LB1B

Low Bay



OVERVIEW

This low bay fixture comes with 5-foot cable attached. It features an integrated heat sink for thermal management. Suitable for locations such as parking ramps, workshops, warehouses, or public transportation platforms.

FEATURES

- Die-cast aluminum body
- IP65
- 1-10V dimming
- Polycarbonate lens



ORDERING INFORMATION

EXAMPLE PN: USL-LB1B-90W-LV-40K-B-H-MS-10V

| USL-LB1B | POWER | VOLTAGE | CCT | FINISH | MOUNTING | OPTIONS | DIMMING |
|----------|------------------|--------------------|------------------|----------------|-----------------------|-------------------------|--------------------------|
| | 60W 60W | LV 100-277V | 30K 3000K | B BLACK | H HOOK | 0 NO SENSOR | 0 NO DIMMING |
| | 90W 90W | | 40K 4000K | W WHITE | J JUNCTION BOX | MS MOTION SENSOR | 10V 1-10V DIMMING |
| | 120W 120W | | 50K 5000K | | | | |
| | 150W 150W | | 57K 5700K | | | | |
| | | | 65K 6500K | | | | |

DISCONTINUED PRODUCTS

EXAMPLE PN: USL-LB1B-90W-LV-50K-B-HOK-3D

| USL-LB1B | POWER | VOLTAGE | CCT | FINISH | MOUNTING | OPTIONS* |
|----------|----------------|--------------------|------------------|----------------|-----------------|---------------------------------------|
| | 60W 60W | LV 100-277V | 50K 5000K | B BLACK | HOK HOOK | 3D TRI-LEVEL MICROWAVE DIMMING |
| | 90W 90W | | | | | |

*Note: Limited stock of discontinued products (USL-LB1B-60W-LV-50K-B-HOK-3D and USL-LB1B-90W-LV-50K-B-HOK-3D) are available.

INTERIOR USL-LB1B

Low Bay



SPECIFICATIONS

| MODEL | OPERATION VOLTAGE | OPERATING TEMPERATURE | RATED LIFESPAN | CCT | CRI | EFFICACY |
|----------|-------------------|-------------------------------|----------------|--------------------------------------|-----|-------------|
| USL-LB1B | 100-277V AC | -22°F – 104°F -30°C – 45°C | 50,000 HOURS | 3000K, 4000K, 5000K, 5700K, 6500K | 80+ | 89-113 lm/W |

| MODEL | POWER (W) | LUMENS (lm) | EFFICACY (lm/W) |
|---------------|-----------|-------------|-----------------|
| USL-LB1B-60W | 60 | 5,311 | 89 |
| USL-LB1B-90W | 90 | 10,200 | 113 |
| USL-LB1B-120W | 120 | 13,300 | 111 |
| USL-LB1B-150W | 150 | 16,100 | 107 |

DIMENSIONS

| MODEL | D DIAMETER | H ₁ HEIGHT | H ₂ HEIGHT W/ MOUNTING | WEIGHT |
|----------|-------------------|-----------------------|-----------------------------------|----------------|
| USL-LB1B | 14.6 in 370 mm | 9.5 in 242 mm | 10.7 in 271 mm | 6.6 lb 3 kg |

