

PROJECT		TYPE		DATE	
---------	--	------	--	------	--

Exterior
 Wet Location
 Non-Dimming
 Dimmable
 10V
 AC
 Up Light
 Down Light
 5 Year Warranty
 DLC
 UL

OVERVIEW

This flood light has a wide range of luminous intensity, making it suitable for a variety of applications. It features a cast aluminum housing with a watertight driver compartment sealed by a gasket.

FEATURES

- Wide range of luminous intensity
- Yoke, slip fitter, trunnion, and knuckle mount options available
- Optional photocell
- 0-10V dimming on select models
- 7Hx6V distribution standard 4Hx4V available on select models
- PF > 90% THD < 20%



ORDERING INFORMATION

EXAMPLE PN: USL-FL81A-100W-LV-50K-D-P-10V-Y

USL-FL81A	POWER ^[1] ^[2]	VOLTAGE ^[2]	CCT	FINISH	PHOTOCELL	DIMMING ^[1]	MOUNTING
15W	15 WATTS	LV 120-277V	30K 3000K	D DARK	O NONE	O NONE	T TRUNNION
27W	27 WATTS	HV 347-480V	40K 4000K	B BRONZE	P WITH	10V 1-10V	K KNUCKLE
45W	45 WATTS		50K 5000K	B BLACK	P PHOTOCELL		Y YOKE
60W	60 WATTS			W WHITE			S SLIP FITTER
70W	70 WATTS						
90W	90 WATTS						
100W	100 WATTS						
135W	135 WATTS						
200W	200 WATTS						
350W	350 WATTS						

[1] Note: dimming not available on 15W-60W models. 70W available in dimming & non-dimming. 90W-350W only available in dimming.

[2] Note: 347V-480V only available with 60W-350W

[3] Note: 135W-350W available in NEMA 4Hx4V distribution

