

EXTERIOR USL-HWP1B Semi Cutoff Wall Pack



OVERVIEW

The US Luminaire semi cut-off wall pack series has been designed and built with high performance, efficiency and cost effectiveness in mind. The LEDs are housed in a sealed compartment separate from the drivers to keep them cool. A bubble level is built in and a gasket is included to ensure proper and simple installation. The unit is lightweight and extremely durable.



FEATURES

- Sealed die-cast profile for indoor and outdoor applications
- Polycarbonate optical lens with UV stabilizers
- Photocell optional
- UL/cUL wet location and DLC qualified
- IP65

ORDERING INFORMATION

EXAMPLE PN: USL-HWP1B-45W-LV-30K-0-D

USL-HWP1B	POWER ^[1] [2] [3]	VOLTAGE ^[1]	CCT ^[2]	CONTROL ^[3]	FINISH
	45W 45 WATTS	LV 100-277V	30K 3000K	O NO PHOTOCELL	D DARK BRONZE
	70W 70 WATTS	HV 200-480V	40K 4000K	P PHOTOCELL	
	100W 100 WATTS		50K 5000K		
	150W 150 WATTS		57K 5700K		
			65K 6500K		

^[1] HV only available with 100W/150W

^[2] 6500K only available with 100W/150W

^[3] Photocell only available with 100/150W

SPECIFICATIONS

MODEL	OPERATION VOLTAGE	OPERATING TEMPERATURE	RATED LIFESPAN	CCT	CRI	EFFICACY
USL-HWPIB	100-277V, 200-480V	-22°F – 113°F -30°C – 45°C	50,000	3000K, 4000K, 5000K, 5700K, 6500K	80+	103-111 lm/W

MODEL	POWER (W)	LUMENS (lm)	EFFICACY (lm/W)	REPLACES MH
USL-HWPIB-45W	45	4,950	110	175-200W
USL-HWPIB-70W	70	7,750	111	200-300W
USL-HWPIB-100W	100	11,000	110	300-400W
USL-HWPIB-150W	150	16,000	107	400W

DIMENSIONS

MODEL	L LENGTH	D DEPTH	H HEIGHT	WEIGHT
USL-HWPIB-45W	13.2 in 335 mm	6.25 in 159 mm	5.4 in 137 mm	6.6 lb 3 kg
USL-HWPIB-70W	14 in 356 mm	7.8 in 200 mm	6.2 in 158 mm	7.7 lb 3.5 kg
USL-HWPIB-100W	14.57 in 370 mm	7.76 in 197 mm	8.94 in 227 mm	13.9 lb 6.3 kg
USL-HWPIB-150W	14.57 in 370 mm	7.76 in 197 mm	8.94 in 227 mm	15 lb 6.8 kg

