

EXTERIOR USL-SLR2T

Rectangular Stadium Light



Exterior

Dimmable

Wet Location

5 Year Warranty

DLC PREMIUM

UL

OVERVIEW

Suitable for use in stadiums, warehouses, and gymnasiums, this product features a high luminous intensity. It is compatible with backup batteries and motion sensors.

FEATURES

- IP65
- PF>0.9
- Modular design
- Adjustable mounting angle



ORDERING INFORMATION

EXAMPLE PN: USL-SLR2T-1000W-LV-50K-15D-0

USL-SLR2T	-	POWER	-	VOLTAGE	-	CCT	-	BEAM ANGLE	-	DIMMING
		300W 300 WATTS		LV 100-277V		40K 4000K		15D 15°		0 NONE
		400W 400 WATTS		HV 200-480V		50K 5000K		25D 25°		10V 0-10V
		600W 600 WATTS				60K 6000K		30D 30°		
		800W 800 WATTS								
		1000W 1000 WATTS								
		1100W 1100 WATTS								

EXTERIOR USL-SLR2T

Rectangular Stadium Light



SPECIFICATIONS

MODEL	OPERATION VOLTAGE	OPERATING TEMPERATURE	RATED LIFESPAN	CCT	CRI	EFFICACY
USL-SLR2T	100-277V 200-480V	-22°F – 113°F -30°C – 45°C	50,000 HOURS	2700-7000K	70+	140 lm/W

MODEL	POWER (W)	LUMENS (lm)	EFFICACY (lm/W)	MH REPLACEMENT
USL-SLR2T-300W	300	42,000	140	400-500
USL-SLR2T-400W	400	56,000	140	600-700
USL-SLR2T-600W	600	84,000	140	900-1,000
USL-SLR2T-800W	800	112,000	140	1,200-1,400
USL-SLR2T-1000W	1000	140,000	140	1,600-1,800
USL-SLR2T-1100W	1100	154,000	140	2000

DIMENSIONS

MODEL	L LENGTH	W WIDTH	T THICKNESS	A MOUNTING HEIGHT	B LIGHT SEGMENT
USL-SLR2T-300W USL-SLR2T-400W	14.4 in 366 mm	30.9 in 787 mm	2.8 in 72 mm	19.3 in 490 mm	5.9 in 151 mm
USL-SLR2T-600W	10.4 in 517 mm				
USL-SLR2T-800W	26.3 in 668 mm				
USL-SLR2T-1000W USL-SLR2T-1100W	32.2 in 819 mm				

