

INTERIOR USL-PL2E Phantom Light



OVERVIEW

These linear fixtures have primarily up light when used with the lens cover. These fixtures are better suited for accent lighting rather than as a primary light source. A pop of color makes these fixtures suitable in environments with children such as schools and children's hospitals.



FEATURES

- Indirect lighting
- Suitable for cove lighting
- TRIAC dimmable
- CCT adjustable
- Seamless connection up to 200W
- UGR<19
- THD<19%
- PF>0.95



ORDERING INFORMATION

EXAMPLE PN: USL-PL2E-2-6W-CA-TRIAC

USL-PL2E	SIZE / POWER	CCT*	DIMMING
	1-3W 1 FT, 3 WATTS	30K 3000K	0 NON-DIMMING
	2-6W 2 FT, 6 WATTS	40K 4000K	TRIAC TRIAC DIMMING
	3-9W 3 FT, 9 WATTS	50K 5000K	
	4-12W 4 FT, 12 WATTS	60K 6000K	
	5-15W 5 FT, 15 WATTS	CA COLOR-ADJUSTABLE	
	6-18W 6 FT, 18 WATTS		
	8-24W 8 FT, 24 WATTS		

*Note: CCT selectable is 3000K/4000K/5000K

ACCESSORIES

USL-PL2E-ACC	ACCESSORY
	N-WHT Narrow white cover (standard)
	N-RED Narrow red cover
	N-GRN Narrow green cover
	N-BLU Narrow blue cover
	N-WHT Wide white cover

INTERIOR USL-PL2E Phantom Light



SPECIFICATIONS

MODEL	OPERATION VOLTAGE	OPERATING TEMPERATURE	RATED LIFESPAN	CCT	CRI	EFFICACY
USL-PL2E	120/240	-14°F – 113°F -10°C – 45°C	50,000 HOURS	3000K, 4000K, 5000K, 6000K	80+	54-91 lm/W

MODEL	POWER (W)	LUMENS (lm) ±10%				EFFICACY (lm/W)
		3000K	4000K	5000K	6000K	
USL-PL2E-1-3W	3	163	168	170	168	54-57
USL-PL2E-2-6W	6	532	537	545	537	89-91
USL-PL2E-3-9W	9	708	710	715	711	79-79
USL-PL2E-4-12W	12	885	890	899	892	74-75
USL-PL2E-5-15W	15	1,115	1,120	1,136	1,124	74-76
USL-PL2E-6-18W	18	1,355	1,364	1,375	1,364	75-76
USL-PL2E-8-24W	24	1,757	1,764	1,776	1,768	73-74

DIMENSIONS

MODEL	L LENGTH	W WIDTH	H HEIGHT
USL-PL2E-1-3W	11.1 in 282 mm	3.1 in 80 mm	1.2 in 30 mm
USL-PL2E-2-6W	22.5 in 571 mm		
USL-PL2E-3-9W	34.6 in 878 mm		
USL-PL2E-4-12W	46.5 in 1181 mm		
USL-PL2E-5-15W	58.3 in 1481 mm		
USL-PL2E-6-18W	68.7 in 1746 mm		
USL-PL2E-8-24W	92.7 in 2355 mm		

PHOTOMETRICS

