

10-Inch Square Canopy Light



PROJECT		TYPE		DATE	
---------	--	------	--	------	--

Exterior Location
 Dimmable
 AC
 Down Light
 5 Year Warranty
 UL
 DLC
 IES

OVERVIEW

Ideally suited for indoor and outdoor applications in parking structures, storage areas, processing plants, indoor stadiums and gas stations, this ultra-slim canopy fixture is certified for wet applications. The driver has thermal overload protection and short circuit protection.



FEATURES

- IP65
- PF > 0.95 and THD < 20%
- 0-10V dimming
- Motion sensor
- Low profile sleek design
- Heat resistant polycarbonate optical lens
- Multiple conduit entry points with two sizes, three 1/2" threaded and one 3/4"



ORDERING INFORMATION

EXAMPLE PN: USL-CNP1B-65W-LV-40K-D-0-0

USL-CNP1B	POWER	VOLTAGE	CCT	FINISH	DIMMING	OPTIONS
	35W 35 WATTS	LV 120-277V	30K 3000K	D DARK BRONZE	0 NONE	0 NONE
	45W 45 WATTS		40K 4000K	W WHITE	10V 0-10V	MS MOTION SENSOR
	65W 65 WATTS		50K 5000K			

DLC# (Version 4.4)
 WSD-CP35W27-40K-[D,W]
 WSD-CP35W27-50K-[D,W]
 WSD-CP45W27-40K-[D,W,B,S]-[Blank,M]
 WSD-CP45W27-40KYY
 WSD-CP45W27-50K-[D,W,B,S]-[Blank,M]
 WSD-CP45W27-50KYY
 WSD-CP45W347-40K-[D,W]
 WSD-CP45W347-50K-[D,W]
 WSD-CP45W48-40K-[D,W,B,S]
 WSD-CP45W48-50K-[D,W,B,S]
 WSD-CP65W27-40K-[D,W,B,S]-[Blank,M]
 WSD-CP65W27-50K-[D,W,B,S]-[Blank,M]

SPECIFICATIONS

MODEL	OPERATION VOLTAGE	OPERATING TEMPERATURE	RATED LIFESPAN	CCT	CRI	EFFICACY
USL-CNP1B	120-277V 347V	-22°F – 113°F -30°C – 45°C	100,000 HOURS	2700K, 3000K 4000K, 5000K	75+	129-132 lm/W

MODEL	POWER (W)	LUMENS (lm) ±10%			EFFICACY (lm/W)
		3000K	4000K	5000K	
USL-CNP1B-35W	35	4,500	4,500	4,575	129-131
USL-CNP1B-45W	45	5,800	5,800	5,925	129-132
USL-CNP1B-65W	65	8,475	8,475	8,525	130-131

DIMENSIONS

MODEL	W WIDTH	H HEIGHT	WEIGHT
ALL	10.05 in 255 mm	3.3in 84 mm	595 lb 2.7 kg

