

EXTERIOR USL-RWPIG Rotatable Wall Pack



OVERVIEW

This wall pack features a rotatable design to direct the light. The higher power options have two segments which are independently movable to create the perfect combination of light output both down and out.

FEATURES

- Rotating design
- IP65
- 25-120W models
- Replaces 100-600W MH fixtures



ORDERING INFORMATION

EXAMPLE PN: USL-RWPIG-25W-1-LV-40K

USL-RWPIG	-	POWER/SIZE	-	VOLTAGE	-	CCT
25W-1		25 WATTS, 1 SEGMENT		LV 100-277V		30K 3000K
40W-1		40 WATTS, 1 SEGMENT				40K 4000K
60W-2		50 WATTS, 2 SEGMENTS				50K 5000K
80W-2		80 WATTS, 2 SEGMENTS				57K 5700K
120W-2		120 WATTS, 2 SEGMENTS				

OLD INVENTORY

EXAMPLE PN: USL-RWPIG-60W-AI-40K

USL-RWPIG	-	POWER/SIZE	-	VOLTAGE	-	CCT
60W		60 WATTS		AI GENERATION 1		40K 4000K
						50K 5000K

*Note: Limited stock is available.

EXTERIOR USL-RWPIG

Rotatable Wall Pack



SPECIFICATIONS

MODEL	OPERATION VOLTAGE	OPERATING TEMPERATURE	RATED LIFESPAN	CCT	CRI	EFFICACY
USL-RWPIG	100-277V	-4°F – 113°F -20°C – 45°C	50,000	4000K, 5000K, 5700K	70+	120-140 lm/W

MODEL	POWER (W)	LUMENS (lm) at:		EFFICACY (lm/W)	REPLACE MH
		4000K	5700K		
USL-RWPIG-25W-1	25	3,250	3,500	130-140	100-150W
USL-RWPIG-40W-1	40	4,800	5,200	120-130	100-250W
USL-RWPIG-60W-A1	60	7,500	8,100	125-135	200-300W
USL-RWPIG-60W-2	60	7,800	8,400	130-140	200-300W
USL-RWPIG-80W-2	80	10,400	11,200	130-140	300-400W
USL-RWPIG-120W-2	120	14,400	15,600	120-130	400-600W

DIMENSIONS

MODEL	L	W	H	WEIGHT
USL-RWPIG-25W-1	9.1 in 232 mm	5.2 in 132 mm	5.7 in 144 mm	4.14 lb 1.88 kg
USL-RWPIG-40W-1				4.45 lb 2.02 kg
USL-RWPIG-60W-A1				4.3 lb 1.95 kg
USL-RWPIG-60W-2	9.1 in 232 mm	5.2 in 132 mm	8.6 in 225 mm	6.79 lb 3.08 kg
USL-RWPIG-80W-2				6.88 lb 3.12 kg
USL-RWPIG-120W-2				7.45 lb 3.38 kg

