

EXTERIOR USL-SL2D Circular Stadium Lights



OVERVIEW

US Luminaire's stadium light series features an architectural design and outstanding durability. Its excellent optics and rugged design allow for use in a variety of indoor and outdoor applications, replacing existing HID and HPS fixtures up to 2000W. Ideal applications include sports field and sports arena lighting, gymnasium lighting, high-mast lighting, and area and storage lighting.



FEATURES

- Die-cast aluminum housing with cooling fins
- Heat and impact resistant tempered glass lens with anti-glare diffuser
- Continuous silicone gasket surrounds lens for IP66 weather-tight seal
- Instant-on flicker-free cold start and hot re-start
- LED engine design with advanced thermal management
- High output LEDs
- Optional laser sight for alignment

ORDERING INFORMATION

EXAMPLE PN: USL-SL2D-750W-LV-65K-10V-40D

USL-SL2D	POWER*	VOLTAGE	CCT	DIMMING	BEAM ANGLE*
	300W 300 WATTS	LV 100-277V	30K 3000K	10V 0-10V	30D 30°
	400W 400 WATTS	HV 277-480V	40K 4000K		40D 40°
	500W 500 WATTS		50K 5000K		60D 60°
	600W 600 WATTS		57K 5700K		
	750W 700 WATTS		65K 6500K		
	1000W 1000 WATTS				
	1250W 1250 WATTS				

*Note:300-600W available with 30/40/60°
600-1250W available with 15/20/25/40/60/80°

ACCESSORIES

USL-SL2D-ACC	ACCESSORY
LSR	Laser sight device with bracket

EXTERIOR USL-SL2D Circular Stadium Lights



SPECIFICATIONS

MODEL	OPERATION VOLTAGE	OPERATING TEMPERATURE	RATED LIFESPAN	CCT	CRI	EFFICACY
USL-SL2D	120-277V 277-480V	-22°F – 113°F -30°C – 45°C	50,000 HOURS	3000K, 4000K, 5000K, 5700K, 6500K	70+	130-150 lm/W

MODEL	POWER (W)	LUMENS (lm)	EFFICACY (lm/W)	CRI	MH EQUIVALENT
USL-SL2D-300W	300	45,000	150	70	500
USL-SL2D-400W	400	60,000	150	70	600
USL-SL2D-500W	500	75,000	150	70	750
USL-SL2D-600W	600	90,000	150	70	1,000
USL-SL2D-750W	750	97,500	130	70	1,200
USL-SL2D-1000W	1000	130,000	130	70	1,500
USL-SL2D-1250W	1250	162,500	130	70	2,000

DIMENSIONS

MODEL	D DIAMETER	L LENGTH	H HEIGHT
USL-SL2D	15.9in 405 mm	16.3 in 415 mm	19.7 in 500 mm

