

# ARCHITECTURAL USL-SCD3Q Crystal Suspended Pendant



PROJECT		TYPE		DATE	
---------	--	------	--	------	--










Architectural Interior Damp Location Dimmable AC Down Light Warranty

## OVERVIEW

The Crystal pendant is circular with down light. It comes standard with 0-10V dimming; TRIAC and DALI are optional. Available as single rings or tiers of 2-5 rings.



## FEATURES

- Damp location
- 160° beam angle
- Direct lights
- Can group 2-5 tiers together
- IP20
- 0-10V dimming

## ORDERING INFORMATION

EXAMPLE PN: USL-SCD3Q-16-15W-35K-10V-S

USL-SCD3Q	SIZE / POWER	CCT	DIMMING	FINISH
<b>16-15W</b>	16 INCH 15 WATTS	<b>30K</b> 3000K	<b>10V</b> 0-10V	<b>W</b> WHITE
<b>24-25W</b>	24 INCH 25 WATTS	<b>35K</b> 3500K	<b>TRI</b> TRIAC	<b>B</b> BLACK
<b>32-35W</b>	32 INCH 35 WATTS	<b>40K</b> 4000K		<b>S</b> SILVER
<b>40-45W</b>	40 INCH 45 WATTS	<b>50K</b> 5000K		<b>###</b> CUSTOM RAL (ENTER CODE)
<b>48-50W</b>	48 INCH 50 WATTS			
<b>60-60W</b>	60 INCH 60 WATTS			

# ARCHITECTURAL USL-SCD3Q Crystal Suspended Pendant



## SPECIFICATIONS

MODEL	OPERATION VOLTAGE	OPERATING TEMPERATURE	RATED LIFESPAN	CCT	CRI	EFFICACY
USL-SCD3Q	120-277V	-4°F – 104°F -20°C – 40°C	50,000 HOURS	3000K, 3500K, 4000K, 5000K	90+	64-70 lm/W

MODEL	POWER (W)	DIAMETER	LUMENS (lm) ±10%				EFFICACY (lm/W)
			3000K	3500K	4000K	5000K	
USL-SCD3Q-16-15W	15	16 inch	958	988	1,019	1,050	64-70
USL-SCD3Q-24-25W	25	24 inch	1,597	1,647	1,698	1,750	64-70
USL-SCD3Q-32-35W	35	32 inch	2,236	2,305	2,377	2,450	64-70
USL-SCD3Q-40-45W	45	40 inch	2,875	2,964	3,056	3,150	64-70
USL-SCD3Q-48-50W	50	48 inch	3,194	3,293	3,395	3,500	64-70
USL-SCD3Q-60-60W	60	60 inch	3,833	3,952	4,074	4,200	64-70

## DIMENSIONS

MODEL	D DIAMETER
USL-SCD3Q-16-15W	15.7 in 400 mm
USL-SCD3Q-24-25W	23.6 in 600 mm
USL-SCD3Q-32-35W	31.5 in 800 mm
USL-SCD3Q-40-45W	39.4 in 1000 mm
USL-SCD3Q-48-50W	47.2 in 1200 mm
USL-SCD3Q-60-60W	59.1 in 1500 mm