

EXTERIOR USL-UGSIJ Square In-Ground Lights



Exterior



DMX



RGB



5 Year
Warranty



OVERVIEW

In-ground light fixtures are optimal for architectural lighting, building facade lighting, and wall washing. Made with die-cast aluminum, stainless steel, corrosion-resistant nylon, and toughened glass, these fixtures are made for durability.

FEATURES

- IP66
- Available in a variety of sizes
- RGB and monochrome options



ORDERING INFORMATION

EXAMPLE PN: USL-UGSIJ-6W-AC-30K-60D

USL-UGSIJ	POWER / VOLTAGE/SIZE*	COLOR / CCT*	BEAM ANGLE
6W-12V	6 WATTS 12V DC 4.72 IN	30K 3000K	10D 10°
6W-AC	6 WATTS 90-265V AC 4.72 IN	60K 6000K	15D 15°
9W-12V	9 WATTS 12V DC 6.3 IN	RGB RGB	25D 25°
9W-AC	9 WATTS 90-265V AC 6.3 IN	BLU BLUE	30D 30°
12W-12V	12 WATTS 12V DC 7.87 IN	GRN GREEN	45D 45°
12W-AC	12 WATTS 90-265V AC 7.87 IN	RED RED	60D 60°

* Please Note: Not all combinations of voltage and colors are available. RGB operates on DC. Single-colored lights operate on AC voltage.

EXTERIOR USL-UGS1J Square In-Ground Lights



SPECIFICATIONS

MODEL	OPERATION VOLTAGE	STORAGE TEMPERATURE	AMBIENT OPERATING TEMP	RATED LIFESPAN	CCT	CRI	EFFICACY
USL-UGS1J	90-265V AC 12V DC	-40°C - 80°C	-40°F - 122°F -40°C - 50°C	50,000 HOURS	3000K, 6000K RGB	80+	90-100 lm/W WHITE 30-70 lm/W COLOR

MODEL	R/G/B QTY	POWER (W)	LUMINOUS FLUX (lm)					
			RED	GREEN	BLUE	RGB	3000K	6000K
USL-UGS1J-6W	2/2/2	6 W	300	420	180	300	540	600
USL-UGS1J-9W	3/3/3	9 W	450	630	270	450	810	900
USL-UGS1J-12W	4/4/4	12 W	600	840	360	600	1,080	1,200

DIMENSIONS

MODEL	TOP DIMENSIONS D1 x D2	HEIGHT H	HOLE WIDTH W1 x W2	DIMENSIONAL DRAWING
USL-UGS1J-6W	4.72 x 4.72 in 120 x 120 mm	3.15 in 80 mm	4.33 x 4.33 in 110 x 110 mm	
USL-UGS1J-9W	6.30 x 6.30 in 160 x 160 mm	3.15 in 80 mm	5.71 x 5.71 in 145 x 145 mm	
USL-UGS1J-12W	7.87 x 7.87 in 200 x 200 mm	3.15 in 80 mm	7.09 x 7.09 in 180 x 180 mm	