



This LED Bed Light replaces the traditional bi-directional fluorescent fixtures used throughout hospitals and the general medical/nursing industry. Two diffuser panels direct light down, up, or in both directions; 44W (4,500 lumens) downlight, 22W (2,250 lumens) uplight, or 66W (6,750 lumens) altogether. A convenient switchable indicator nightlight is provided next to the pull chain switches, which can be extended to customize the chain length and reach. A 50,000 hour lifespan with a 5 year warranty will ensure that this fixture will continue to run for many years of dependable service.

Features

- Selectable Bi-directional up/down lights
- Nightlight indicator light adjacent to pull switch
- No UV or IR radiation
- Minimalistic and efficient design
- Mercury-free construction
- Suitable for Damp Location use
- Easy and secure installation

Applications

- Patient bed overhead lighting
- Overhead task lighting
- Bi-directional area lighting
- General lighting

Specification

Model Number	USL-BL2Z-64W-40K
Beam Angle	Independent up/down°
Lumen Output	6750 (4500 down+2250 up) LM
Luminous Efficacy	105 LM/W
Input Power	64 W
Input Voltage	120 Vac
Power Factor	0.99
THD	0.1
Color Temp (CCT)	4000 K
Color Rend (CRI)	>80
Lifetime Rating	50000 hours
Warranty	5 Years
Dimmability	No
Operating Temp	-4 to 104 (°F)
Environment	Damp Location
DLC	DLC Standard
Safety Cert	UL
Weight	6.8 LBS
Dimensions	48.6"x4.6"x4.6"