

PROJECT		TYPE		DATE	
---------	--	------	--	------	--

							
Interior	Damp Location	Dimmable	AC	Down Light	Warranty		

OVERVIEW

This back-lit panel is recessed mount. Available in 2x2 and 2x4.

FEATURES

- Recessed mount
- 120° beam angle
- PF > 0.9



ORDERING INFORMATION

EXAMPLE PN: USL-FPR1F-2X2-40W-40K-10V

USL-FPR1F	SIZE / POWER	CCT	DIMMING
	2X2-40W 2X2, 40 WATTS	35K 3500K	10V 0-10V
	2X4-50W 2X4, 50 WATTS	40K 4000K	
		50K 5000K	

*Note: 4000K and 5000K are standard.

INTERIOR USL-FPRIF

Back-Lit Recessed Flat Panel



SPECIFICATIONS

MODEL	OPERATION VOLTAGE	OPERATING TEMPERATURE	CCT	CRI	EFFICACY
USL-FPRIF	120-277V AC	-4°F – 104°F -20°C – 40°C	3500K, 4000K, 5000K	80+	100 lm/W

MODEL	POWER (W)	LUMENS (lm) ±10%	EFFICACY (lm/W)
USL-FPRIF-2X2-40W	40	4,000	100
USL-FPRIF-2X4-50W	50	5,000	100

DIMENSIONS

MODEL	L LENGTH	W WIDTH	H HEIGHT
USL-FPRIF-2X2	23.74 in 603 mm	23.74 in 603 mm	1.97 in 50 mm
USL-FPRIF-2X4	47.72 in 1212 mm		

