

# EXTERIOR USL-WWLR1D Linear RGB Wall Washer



Exterior



Wet Location



5 Year Warranty



## OVERVIEW

US Luminaire's series of RGB linear wall washers are ideally suited for bars, restaurants, hotels and stages. Available in both 20" and 40", up to 275W can be daisy-chained together for a grand scheme.

## FEATURES

- IP65
- Projection distance 15-30 m
- Aluminum shell improves thermal management
- Tempered glass protects against dust and humidity



## ORDERING INFORMATION

EXAMPLE PN: USL-WWLR1D-22W-RGB-8D

USL-WWLR1D	POWER*	CCT*	BEAM ANGLE
<b>22W</b>	22 WATTS, 20 INCHES	<b>30K</b>	<b>8D</b>
<b>45W</b>	45 WATTS, 40 INCHES	<b>40K</b>	<b>12D</b>
		<b>60K</b>	<b>30D</b>
		<b>BLU</b>	<b>45D</b>
		<b>GRN</b>	<b>60D</b>
		<b>RGB</b>	<b>15X50</b>

# EXTERIOR USL-WWLRID Linear RGB Wall Washer



## SPECIFICATIONS

MODEL	OPERATION VOLTAGE	AMBIENT OPERATING TEMP	RATED LIFESPAN	CCT	CRI	EFFICACY
USL-WWLRID	24V	-4°F – 104°C -20°C – 40°C	50,000 HOURS	2700-3200K 4000-4500K 5500-6500K, RGB	70+	45-62 lm/W WHITE 12-60 lm/W RGB

MODEL	POWER (W)	LUMENS (lm)	CCT	MAX CURRENT (A)	EFFICACY (lm/W)
USL-WWLRID-22W-30K	22	1,260	2700-3200K	0.9	57
USL-WWLRID-22W-40K	22	1,300	4000-4500K	0.9	59
USL-WWLRID-22W-60K	22	1,380	5500-6500K	0.9	62
USL-WWLRID-22W-B	22	260	BLUE	0.9	16
USL-WWLRID-22W-G	22	860	GREEN	0.9	53
USL-WWLRID-22W-RGB	22	840	RGB	0.9	38
USL-WWLRID-45W-30K	45	2,100	2700-3200K	1.87	46
USL-WWLRID-45W-40K	45	2,200	4000-4500K	1.87	48
USL-WWLRID-45W-60K	45	2,400	5500-6500K	1.87	53
USL-WWLRID-45W-B	45	420	BLUE	1.87	16
USL-WWLRID-45W-G	45	1,500	GREEN	1.87	52
USL-WWLRID-45W-RGB	45	1,950	RGB	1.87	47

## DIMENSIONS

	22W	45W	DIMENSIONAL DRAWINGS
<b>A</b> ADDITIONAL LENGTH	0.906 in / 23.0 mm	0.906 in / 23.0 mm	
<b>D</b> CENTER-CENTER BETWEEN LEDS	1.063 in / 27.0 mm	1.063 in / 27.0 mm	
<b>H1</b> TOTAL HEIGHT	1.969 in / 50.0 mm	1.969 in / 50.0 mm	
<b>H2</b> LIGHT BAR HEIGHT	1.075 in / 27.3 mm	1.075 in / 27.3 mm	
<b>H3</b> BRACKET HEIGHT	1.378 in / 35.0 mm	1.378 in / 35.0 mm	
<b>L1</b> TOTAL LENGTH	21.890 in / 556 mm	41.18 in / 1046 mm	
<b>L2</b> LIGHT BAR LENGTH	20.079 in / 510 mm	39.37 in / 1000 mm	
<b>W</b> LIGHT BAR WIDTH	1.949 in / 49.5 mm	1.949 in / 49.5 mm	