

INTERIOR USL-SLED1R Wraparound Strip Light



OVERVIEW

This linear strip fixture is suitable for a wide range of applications such as storage and utility areas, cove lighting, display cases, and task or general lighting. It can be surface mounted or pendant mounted.



FEATURES

- IP20
- Surface mount or pendant mount with aircraft cable
- Optional emergency battery supplies 90 minutes of power
- Steel housing
- PF>0.92
- THD<20%

ORDERING INFORMATION

EXAMPLE PN: USL-SLED1R-4-36W-40K-F-10V-C-EO

USL-SLED1R	LENGTH/POWER	CCT	LENS	DIMMING	MOUNTING	OPTIONS
	4-24W 4 FT, 24W	40K	F FROSTED	10V 0-10V	O SURFACE MOUNT	O NONE
	4-36W 4 FT, 36W	50K			C 36IN CHAIN	EM EMERGENCY POWER
	8-48W 8 FT, 48W				A AIRCRAFT CABLE	OS OCCUPANCY SENSOR
	8-72W 8 FT, 72W				W WIRE GUARD	OD OCCUPANCY SENSOR, DAYLIGHT SENSOR
						EO EMERGENCY POWER, OCCUPANCY SENSOR
						ED EMERGENCY, OCCUPANCY, DAYLIGHT SENSOR

INTERIOR USL-SLED1R

Wraparound Strip Light



SPECIFICATIONS

MODEL	OPERATION VOLTAGE	OPERATING TEMPERATURE	RATED LIFESPAN	CCT	CRI	EFFICACY
USL-SLED1R	120-277V	-4°F – 122°F -20°C – 50°C	50,000 HOURS	4000K, 5000K	80+	131-139 lm/W

MODEL	POWER (W)	CCT	LUMENS (lm)	EFFICACY (lm/W)
USL-SLED1R-4-24W-40K	24	4000K	3,309	138
USL-SLED1R-4-24W-50K	24	5000K	3,324	139
USL-SLED1R-4-36W-40K	36	4000K	4,712	131
USL-SLED1R-4-36W-50K	36	5000K	4,741	132
USL-SLED1R-8-48W-40K	48	4000K	6,619	138
USL-SLED1R-8-48W-50K	48	5000K	6,638	138
USL-SLED1R-8-72W-40K	72	4000K	9,424	131
USL-SLED1R-8-72W-50K	72	5000K	9,475	132

DIMENSIONS

MODEL	L LENGTH	W WIDTH	H HEIGHT
USL-SLED1R-4	48 in 1220 mm	3.2 in 81 mm	3.4 in 86 mm
USL-SLED1R-8	96 in 2438 mm	3.2 in 81 mm	3.4 in 86 mm

