

# EXTERIOR USL-LWWID Linear Wall Washer

with 3-in-1 RGB



Exterior



Wet Location



5 Year  
Warranty

## OVERVIEW

This series of RGB linear wall washers features a 3-in-1 RGB LED. It is ideally suited for bars, restaurants, hotels and stages. Available in both 20" and 40", up to 275W can be daisy-chained together for a grand scheme.

## FEATURES

- IP65
- 3-in-1 RGB LEDs
- Projection distance 15-30 m
- Aluminum shell improves thermal management
- Tempered glass protects against dust and humidity



## ORDERING INFORMATION

EXAMPLE PN: USL-LWWID-15W-RGB-15D

USL-LWWID	POWER*	CCT*	BEAM ANGLE		
<b>15W</b>	15 WATTS, 20 INCHES	<b>30K</b>	2700-3200K	<b>15D</b>	15°
<b>22W</b>	22 WATTS, 20 INCHES	<b>40K</b>	4000-4500K	<b>25D</b>	25°
<b>30W</b>	30 WATTS, 40 INCHES	<b>60K</b>	5500-6500K	<b>45D</b>	45°
<b>45W</b>	45 WATTS, 40 INCHES	<b>BLU</b>	BLUE		
<b>60W</b>	60 WATTS, 40 INCHES	<b>GRN</b>	GREEN		
		<b>RED</b>	RED		
		<b>YEL</b>	YELLOW		
		<b>RGB3</b>	RGB 3-IN-1		

\*Note: Not all combinations of power and CCT are available. Please see specification table for valid options.

# EXTERIOR USL-LWWID Linear Wall Washer

with 3-in-1 RGB



## SPECIFICATIONS

MODEL	OPERATION VOLTAGE	AMBIENT OPERATING TEMP	RATED LIFESPAN	CCT	CRI	EFFICACY
USL-LWWID	24V	-4°F - 104°C -20°C - 40°C	50,000 HOURS	2700-3200K 4000-4500K 5500-6500K, RGB	70+	36-53 lm/W WHITE 16-46 lm/W COLOR

MODEL	POWER (W)	LUMENS (lm)	CCT	MAX CURRENT (A)	EFFICACY (lm/W)
USL-LWWID-22W-30K	22	800	2700-3200K	0.9	36
USL-LWWID-22W-40K	22	1,010	4000-4500K	0.9	46
USL-LWWID-22W-60K	22	1,050	5500-6500K	0.9	48
USL-LWWID-22W-BLU	22	380	BLUE	0.9	17
USL-LWWID-22W-GRN	22	980	GREEN	0.9	45
USL-LWWID-22W-RED	15	520	RED	0.625	35
USL-LWWID-22W-YEL	15	450	YELLOW	0.625	30
USL-LWWID-22W-RGB3	22	367	RGB	0.9	17
USL-LWWID-45W-30K	45	1,700	2700-3200K	1.87	38
USL-LWWID-45W-40K	45	2,200	4000-4500K	1.87	49
USL-LWWID-45W-60K	45	2,400	5500-6500K	1.87	53
USL-LWWID-45W-BLU	45	726	BLUE	1.87	16
USL-LWWID-45W-GRN	45	2,060	GREEN	1.87	46
USL-LWWID-45W-RED	30	1,030	RED	1.25	34
USL-LWWID-45W-YEL	30	980	YELLOW	1.25	33
USL-LWWID-45W-RGB3	30	520	RGB	1.25	17
USL-LWWID-60W-RGB3	60	1,025	RGB	2.5	17

## DIMENSIONS

	15/22W	30/45/60W	DIMENSIONAL DRAWINGS
<b>A</b> ADDITIONAL LENGTH	0.083 in / 2.1 mm	0.083 in / 2.1 mm	
<b>D</b> CENTER-CENTER BETWEEN LEDS	1.106 in / 28.1 mm	1.106 in / 28.1 mm	
<b>H1</b> TOTAL HEIGHT	2.867 in / 72.8 mm	2.867 in / 72.8 mm	
<b>H2</b> LIGHT BAR HEIGHT	1.606 in / 40.8 mm	1.606 in / 40.8 mm	
<b>H3</b> BRACKET HEIGHT	1.260 in / 32.0 mm	1.260 in / 32.0 mm	
<b>L1</b> TOTAL LENGTH	20.039 in / 509 mm	39.528 in / 1004 mm	
<b>W</b> LIGHT BAR WIDTH	2.323 in / 59.0 mm	2.323 in / 59.0 mm	