

INTERIOR USL-T5BL2E Slim Batten Strip Light



PROJECT	TYPE	DATE
---------	------	------



OVERVIEW

This slim batten light can replace T8 and T12 fluorescent fixtures. It can be surface mounted or ceiling suspended. Multiple segments can be hooked together (up to 200W) to create longer lengths using either a cable or seamless connector.



FEATURES

- IP40
- Isolated driver
- Aluminum body for heat dissipation
- PF>0.9
- THD<20%
- 120° beam angle

ORDERING INFORMATION

EXAMPLE PN: USL-T5BL2E-3-25W-40K-F-N-LV

USL-T5BL2E	SIZE / POWER	CCT	LENS	DIMMING/VOLTAGE
2-15W	2 FT, 15W	30K 3000K	C CLEAR	N-LV NON-DIMMING, 120-277V AC
3-25W	3 FT, 25W	40K 4000K	F FROSTED	D-LV DIMMABLE, 120V AC
4-30W	4 FT, 30W	50K 5000K		
5-40W	5 FT, 40W			
6-44W	6 FT, 44W			
8-60W	8 FT, 60W			

ACCESSORIES

USL-T5BL2E-ACC	ACCESSORY
SUSPKIT	Suspension kit, 2 pieces, 1m standard length
PWR	2m power cable, with pigtail

INTERIOR USL-T5BL2E

Slim Batten Strip Light



SPECIFICATIONS

MODEL	OPERATION VOLTAGE	OPERATING TEMPERATURE	RATED LIFESPAN	CCT	CRI	EFFICACY
USL-T5BL2E	120-277V AC	-22°F – 122°F -20°C – 50°C	50,000 HOURS	3000K, 4000K, 5000K	80+	100-120 lm/W

MODEL	POWER (W)	LUMENS - FROSTED (lm)	LUMENS - CLEAR (lm)	EFFICACY (lm/W)
USL-T5BL2E-2-15W	15	1,500	1,800	100-120
USL-T5BL2E-3-25W	25	2,500	3,000	100-120
USL-T5BL2E-4-30W	30	3,000	3,600	100-120
USL-T5BL2E-5-40W	40	4,000	4,800	100-120
USL-T5BL2E-6-44W	44	4,400	5,280	100-120
USL-T5BL2E-8-60W	60	6,000	7,200	100-120

DIMENSIONS

MODEL	L	W	H
USL-T5BL2E-2-15W	21.6 in 549 mm	1.6 in 41 mm	1.4 in 36 mm
USL-T5BL2E-3-25W	33.6 in 853 mm		
USL-T5BL2E-4-30W	45.2 in 1149 mm		
USL-T5BL2E-5-40W	58.4 in 1483 mm		
USL-T5BL2E-6-44W	70.2 in 1782 mm		
USL-T5BL2E-8-60W	89.9 in 2284 mm		

