

EXTERIOR USL-UGC1J

Circular In-Ground Lights



Exterior



DMX



RGB



5 Year Warranty



OVERVIEW

In-ground light fixtures are optimal for architectural lighting, building facade lighting, and wall washing. Made with die-cast aluminum, stainless steel, corrosion-resistant nylon, and toughened glass, these fixtures are made for durability.

FEATURES

- IP66
- Available in a variety of sizes
- RGB and monochrome options



ORDERING INFORMATION

EXAMPLE PN: USL-UGC1J-15W-24V-RGB-30D

USL-UGC1J	POWER / VOLTAGE/DIAMETER*				COLOR / CCT*		BEAM ANGLE	
3W-12V	3 WATTS	12V DC	4.72 IN	30K	3000K	10D	10°	
3W-AC	3 WATTS	90-265V AC	4.72 IN	60K	6000K	15D	15°	
4W-12V	4 WATTS	12V DC	4.72 IN	RGB	RGB	25D	25°	
4W-AC	4 WATTS	90-265V AC	4.72 IN	BLU	BLUE	30D	30°	
6W-12V	6 WATTS	12V DC	5.91 IN	GRN	GREEN	45D	45°	
6W-AC	6 WATTS	90-265V AC	5.91 IN	RED	RED	60D	60°	
9W-12V	9 WATTS	12V DC	5.91 IN					
9W-AC	9 WATTS	90-265V AC	5.91 IN					
12W-12V	12 WATTS	12V DC	5.91 IN					
12W-AC	12 WATTS	90-265V AC	5.91 IN					
15W-24V	15 WATTS	24V DC	7.87 IN					
15W-AC	15 WATTS	90-265V AC	7.87 IN					
18W-24V	18 WATTS	24V DC	7.87 IN					
18W-AC	18 WATTS	90-265V AC	7.87 IN					
24W-24V	24 WATTS	24V DC	9.84 IN					
24W-AC	24 WATTS	90-265V AC	9.84 IN					
36W-24V	36 WATTS	24V DC	11.81 IN					
36W-AC	36 WATTS	90-265V AC	11.81 IN					

* Please Note: Not all combinations of voltage and colors are available. RGB operates on DC (5V, 12V, or 24V depending on model).

Single-colored lights operate on AC voltage.

EXTERIOR USL-UGCIJ

Circular In-Ground Lights



SPECIFICATIONS

MODEL	OPERATION VOLTAGE	STORAGE TEMPERATURE	AMBIENT OPERATING TEMP	RATED LIFESPAN	CCT	CRI	EFFICACY
USL-UGCIJ	90-265V AC 5V, 12V, 24V DC	-40°F – 176°F -40°C – 80°C	-40°F – 122°F -40°C – 50°C	50,000 HOURS	3000K, 6000K RGB	80+	90-100 lm/W WHITE 30-70 lm/W COLOR

MODEL	R/G/B QTY	POWER (W)	LUMINOUS FLUX (lm)					
			RED	GREEN	BLUE	RGB	3000K	6000K
USL-UGCIJ-3W	1/1/1	3	150	210	90	150	270	300
USL-UGCIJ-4W	2/1/1	4	200	280	120	200	360	400
USL-UGCIJ-6W	2/2/2	6	300	420	180	300	540	600
USL-UGCIJ-9W	3/3/3	9	450	630	270	450	810	900
USL-UGCIJ-12W	4/4/4	12	600	840	360	600	1,080	1,200
USL-UGCIJ-15W	5/5/5	15	750	1,050	450	750	1,350	1,500
USL-UGCIJ-18W	6/6/6	18	900	1,260	540	900	1,620	1,800
USL-UGCIJ-24W	8/8/8	24	1,200	1,680	720	1200	2,160	2,400
USL-UGCIJ-36W	12/12/12	38	1,800	2,520	1,080	1,800	3,240	3,600

DIMENSIONS

MODEL	DIAMETER D	HEIGHT H	WIDTH W	DIMENSIONAL DRAWING
USL-UGCIJ-3W	4.72 in 120 mm	3.15 in 80 mm	3.94 in 100 mm	
USL-UGCIJ-4W	4.72 in 120 mm	3.15 in 80 mm	3.94 in 100 mm	
USL-UGCIJ-6W	5.91 in 150 mm	3.54 in 90 mm	5.31 in 135 mm	
USL-UGCIJ-9W	7.09 in 180 mm	3.54 in 90 mm	6.30 in 160 mm	
USL-UGCIJ-12W	7.09 in 180 mm	3.54 in 90 mm	5.91 in 150 mm	
USL-UGCIJ-15W	7.87 in 200 mm	3.54 in 90 mm	5.91 in 150 mm	
USL-UGCIJ-18W	7.87 in 200 mm	3.54 in 90 mm	7.09 in 180 mm	
USL-UGCIJ-24W	9.84 in 250 mm	3.94 in 100 mm	9.06 in 230 mm	
USL-UGCIJ-36W	11.81 in 300 mm	3.94 in 100 mm	11.02 in 280 mm	