

PROJECT	TYPE	DATE
---------	------	------

 Interior
  Damp Location
  Dimmable
  AC
  Down Light
  Color Select
  2.4 GHz
  5 Year Warranty
  UL
  DLC

OVERVIEW

This edge-lit panel is CCT selectable at 3000K, 3500K, 4000K, and 5000K. It is controlled by a wall switch or a 2.4 GHz hand-held remote. The fixture utilizes a PMMA LGP to prevent yellowing over time.



FEATURES

- IP44
- PMMA light guide panel
- 2.4 GHz wireless dimming
- CCT selectable via remote
- PF > 0.95
- 120° angle

ORDERING INFORMATION

EXAMPLE PN: USL-TFP2P-2X4-50W-CS

USL-TFP2P	SIZE / POWER	CCT
1X4-40W	1X4, 40 WATTS (DLC)	CS CCT SELECTABLE 3000K-5000K
1X4-45W	1X4, 45 WATTS	
2X2-36W	2X2, 36 WATTS	
2X2-40W	2X2, 40 WATTS (DLC)	
2X2-45W	2X2, 45 WATTS	
2X4-50W	2X4, 50 WATTS (DLC)	
2X4-60W	2X4, 60 WATTS (DLC)	

ACCESSORIES

USL-TFP2P	ACCESSORY
RMT	hand-held remote
DIM	dimmer wall switch

INTERIOR USL-TFP2P 2.4 GHz CCT Tunable Flat Panel



SPECIFICATIONS

MODEL	OPERATION VOLTAGE	OPERATING TEMPERATURE	RATED LIFESPAN	CCT	CRI	EFFICACY
USL-TFP2P	120-277V AC	-4°F – 113°F -20°C – 45°C	50,000 HOURS	3000K-500K TUNABLE	80+	110 lm/W

MODEL	DLC	SIZE	POWER (W)	LUMENS (lm) ±10%	EFFICACY (lm/W)
USL-TFP2P-1X4-40W	✓	1x4	40	4,400	110
USL-TFP2P-1X4-45W			45	4,950	110
USL-TFP2P-2X2-36W		2x2	36	3,960	110
USL-TFP2P-2X2-40W	✓		40	4,400	110
USL-TFP2P-2X2-45W			45	4,950	110
USL-TFP2P-2X4-50W	✓	2x4	50	5,500	110
USL-TFP2P-2X4-60W	✓		60	6,600	110

DIMENSIONS

MODEL	L LENGTH	W WIDTH	H HEIGHT	WEIGHT
USL-TFP2P-2X2	23.7 in 603 mm	23.7 in 603 mm	0.39 in 10 mm	3.3 kg
USL-TFP2P-2X4	47.8 in 1213 mm			6.3 kg
USL-TFP2P-1X4		11.9 in 301 mm		3.8 kg