


INTERIOR USL-VTIF Volumetric Troffer



PROJECT		TYPE		DATE	
---------	--	------	--	------	--



OVERVIEW

This troffer is suitable for both new construction and retrofit applications. It can be used in applications such as office spaces, retail stores, education, government, healthcare, and hospitality.

FEATURES

- Recessed mounting
- Suitable for suspended ceilings
- 0-10V dimming (20-100%)
- PF > 0.9
- THD < 20%
- 2x2 and 2x4



X Non insulation-contact rated

ORDERING INFORMATION

EXAMPLE PN: USL-VTIF-2X2-35W-LV-40K-10V

USL-VTIF	SIZE / POWER	VOLTAGE	CCT	DIMMING
	2X2-35W 2X2, 35 WATTS	LV 100-277V	35K 3500K	10V 0-10V DIMMING
	2X4-48W 2X4, 48 WATTS		40K 4000K	
			50K 5000K	

INTERIOR USL-VT1F

Volumetric Troffer



SPECIFICATIONS

MODEL	OPERATION VOLTAGE	RATED LIFESPAN	CCT	CRI	EFFICACY
USL-VT1F	100-277V	50,000 HOURS	3500K, 4000K, 5000K	80	125

MODEL	POWER (W)	SIZE	LUMENS (lm) ±10%	EFFICACY (lm/W)
USL-VT1F-2X2-35W	35	2X2	4,375	125
USL-VT1F-2X4-48W	48	2X4	6,000	125

DIMENSIONS

MODEL	L LENGTH	W WIDTH	H HEIGHT
2X2	23.7 in 602 mm	23.8 in 604 mm	2.8 in 71 mm
2X4	47.7 in 1212		

