

EXTERIOR USL-SWPM2H Solar Rotatable Wall Pack



PROJECT	TYPE	DATE
---------	------	------



Exterior Wet Location Battery Option Down Light Warranty

OVERVIEW

This solar wall pack is rotatable with a range of 45 degrees. Its small form factor makes it suitable for use on residential garages, fences, and walkways near buildings.

FEATURES

- Adjustable angle
- PIR has 120° detection 15 feet away
- IP65, IK06
- Turns on at 50 lux (4.64 fc) ambient
- Turns off at 10 lux (0.93 fc) ambient



ORDERING INFORMATION

EXAMPLE PN: USL-SWPM2H-10W-30K

USL-SWPM2H	-	POWER	-	CCT
		10W	10 WATTS	30K 3000K

EXTERIOR USL-SWPM2H
Solar Rotatable Wall Pack



SPECIFICATIONS

MODEL	OPERATION VOLTAGE	CHARGING TEMPERATURE	DISCHARGING TEMPERATURE	RATED LIFESPAN	CCT	EFFICACY
USL-SWPM2H	3.7V BATTERY	32°F – 113°F 0°C – 45°C	-4°F – 140°F -20°C – 60°C	1,500 CYCLES	4000K	100 lm/W

MODEL	LED POWER (W)	SOLAR POWER (W)	LI-ION BATTERY	MOUNTING HEIGHT	REPLACES MH	LUMENS (lm) ±10%	EFFICACY (lm/W)
USL-SWPM2H-10W	10	0.5	3.7 V, 2 Ah	7-10 FT	10 FT	1,000	100

DIMENSIONS

MODEL	W WIDTH	D DEPTH	H HEIGHT	WEIGHT
ALL	3.5 in 90 mm	2.2 in 55 mm	3.1 in 79.5 mm	0.7 lbs 0.3 kg

