

INTERIOR USL-FCIT

Flat Center Troffer



PROJECT		TYPE		DATE	
---------	--	------	--	------	--



OVERVIEW

This troffer features a flat diffuser down the middle of the fixture, creating indirect light and reducing glare. It is ideal for replacing fluorescent troffers in offices, retail, and educational locations.

FEATURES

- 0-10V dimming
- IP20
- Low glare
- Indirect light



ORDERING INFORMATION

EXAMPLE PN: USL-FCIT-2X4-65W-LV-50K-10V

USL-FCIT	SIZE/POWER	VOLTAGE	CCT	DIMMING
	2X2-27W 2X2, 27 WATTS	LV 100-277V	40K 4000K	10V 0-10V
	2X4-65W 2X4, 65 WATTS		50K 5000K	

INTERIOR USL-FCIT

Flat Center Troffer



SPECIFICATIONS

MODEL	OPERATION VOLTAGE	RATED LIFESPAN	CCT	CRI	EFFICACY
USL-FCIT	100-277V	50,000 HOURS	4000K, 5000K	80+	104-108 lm/W

MODEL	POWER (W)	LUMENS (lm)	EFFICACY (lm/W)
USL-FCIT-2X2	27	2,810	104
USL-FCIT-2X4	65	7,010	108

DIMENSIONS

MODEL	L LENGTH	W WIDTH	H HEIGHT
USL-FCIT-2X2	23.82 in 605 mm	23.82 in 605 mm	3.94 in 100 mm
USL-FCIT-2X4	47.72 in 1212 mm	23.82 in 605 mm	3.94 in 100 mm

