

Mounting Accessories for 2 3/8" Tenon



OVERVIEW

These mounting accessories can be used to mount 1-4 fixtures. These adapt to existing 4" or 5" round and square poles. It also supports wall mounting. Supports 2 3/8" tenon.

COMPATIBLE PRODUCTS

- USL-FLLIA High Intensity Flood Light
- USL-FL8IA General Purpose Flood Light
- USL-AL2IC 1-Arm Circular Post Light (certain models)
- USL-ALIC 3-Arm Circular Post Light (certain models)



ORDERING INFORMATION

EXAMPLE PN: USL-MNTIA-ACC-4SQ-SP-D

USL-MNTIA-ACC	SIZE / POWER	FINISH
4SQ-SP	4" SQUARE POLE MOUNT WITH 2-3/8" O.D. TENON	D DARK BRONZE
4SQR-SP	4" ROUND POLE MOUNT WITH 2-3/8" O.D. TENON	
5SQ-SP	5" SQUARE POLE MOUNT WITH 2-3/8" O.D. TENON	
5SQR-SP	5" ROUND POLE MOUNT WITH 2-3/8" O.D. TENON	
SP-TR	POLE BRACKET ACCESSORIES-TENON & YOKE ADAPTER	
WM-SP	90° WALL MOUNT BRACKET WITH 2-3/8" O.D. TENON	
SQ-SP	2-3/8" OD HORIZONTAL TENON MID-POLE BRACKET	
R60-SP2-90	DOUBLE 90° HORIZONTAL TENON ADAPTER	
R60-SP2-180	DOUBLE 180° HORIZONTAL TENON ADAPTER	
R60-SP3-90	TRIPLE 90° HORIZONTAL TENON ADAPTER	
R60-SP3-120	TRIPLE 120° HORIZONTAL TENON ADAPTER	
R60-SP4-90	QUAD 90° HORIZONTAL TENON ADAPTER	

Mounting Accessories for 2 3/8" Tenon



POLE BRACKET FOR MOUNTING ONE FIXTURE ON AN EXISTING POLE

USL-MNTIA-ACC-4SQ-SP-D

4" Square Pole Mount with 2-3/8" O.D. Tenon

For use with square, non-tapered steel and aluminum poles. Furnished with four 5/16" hex head stainless steel bolts. Vertical tenon measures 2-3/8" O.D. and is made of steel tubing. Fixtures mounted to this bracket can be adjusted both vertically and horizontally.



USL-MNTIA-ACC-4SQR-SP-D

4" Round Pole Mount with 2-3/8" O.D. Tenon

For use with Round, non-tapered steel and aluminum poles. Furnished with three 3/8" hex head stainless steel bolts. Vertical tenon measures 2-3/8" O.D., and is made of steel tubing. Fixtures mounted to this bracket can be adjusted both vertically and horizontally.



USL-MNTIA-ACC-5SQ-SP-D

5" Square Pole Mount with 2-3/8" O.D. Tenon

For use with square, non-tapered steel and aluminum poles. Furnished with four 5/16" hex head stainless steel bolts. Vertical tenon measures 2-3/8" O.D. and is made of steel tubing. Fixtures mounted to this bracket can be adjusted both vertically and horizontally.



USL-MNTIA-ACC-5SQR-SP-D

5" Round Pole Mount with 2-3/8" O.D. Tenon

For use with Round, non-tapered steel and aluminum poles. Furnished with three 3/8" hex head stainless steel bolts. Vertical tenon measures 2-3/8" O.D., and is made of steel tubing. Fixtures mounted to this bracket can be adjusted both vertically and horizontally.



USL-MNTIA-ACC-SP-TR-D

Pole Bracket accessories-Tenon & Yoke Adapter

The 2-3/8" OD Tenon Mount Adapter for Yoke Fixtures is designed to mount light fixtures that are equipped with a yoke mount onto a 2-3/8" OD tenon.



Mounting Accessories for 2 3/8" Tenon



ROUND TENON FOR MOUNTING 2-4 FIXTURES ON AN EXISTING POLE

USL-MNT1A-ACC-R60-SP2-90-D

Double 90° Horizontal Tenon Adapter

The Bracket is designed to mount over 2-3/8" (60mm) O.D. vertical tenon. Two fixtures can be mounted to the Round External Mount Horizontal Tenon and adjusted horizontally



USL-MNT1A-ACC-R60-SP2-180-D

Double 180° Horizontal Tenon Adapter

The Bracket is designed to mount over 2-3/8" (60mm) O.D. vertical tenon. Two fixtures can be mounted to the Round External Mount Horizontal Tenon and adjusted horizontally



USL-MNT1A-ACC-R60-SP3-90-D

Triple 90° Horizontal Tenon Adapter

The Bracket is designed to mount over 2-3/8" (60mm) O.D. vertical tenon. Three fixtures can be mounted to the Round External Mount Horizontal Tenon and adjusted horizontally



USL-MNT1A-ACC-R60-SP3-120-D

Triple 120° Horizontal Tenon Adapter

The Bracket is designed to mount over 2-3/8" (60mm) O.D. vertical tenon. Three fixtures can be mounted to the Round External Mount Horizontal Tenon and adjusted horizontally



USL-MNT1A-ACC-R60-SP4-90-D

Quad 90° Horizontal Tenon Adapter

The Bracket is designed to mount over 2-3/8" (60mm) O.D. vertical tenon. Four fixtures can be mounted to the Round External Mount Horizontal Tenon and adjusted horizontally



Mounting Accessories for 2 3/8" Tenon




WALL BRACKET FOR MOUNTING ONE FIXTURE ON A FLAT SURFACE

USL-MNTIA-ACC-ACC-WM-SP-D

90° Wall Mount Bracket with 2-3/8" O.D. Tenon

The 90° wall mount bracket with 2-3/8" tenon attaches a light to almost any surface: wall, roof, or wood pole. Provides wiring access and a built-in 2-3/8" O.D. tenon to mount a fixture with our adjustable slipfitter. Suggested 3/8" diameter bolts for mounting. Mounting holes are spaced 3-1/4" apart.



USL-MNTIA-ACC-SQ-SP-D

2-3/8" OD Horizontal Tenon Mid-Pole Bracket

2-3/8" OD Horizontal Tenon Mid-Pole Bracket is designed to mount light fixture that is equipped with an adjustable slipfitter onto a 2-3/8" OD horizontal tenon.

