

USL-DC82S

Ceiling Fixture & Pendant

Features

Housing

Die-formed Cold-rolled Steel
Inner Shade: Off White Decorative Fibre Linen
Outer Shade: Semi-clear Silver Decorative Fibre Linen

Optical

Shade: High Transmission Acrylic Front Panel Create Excellent Light Distribution and Uniformity
LED: High Efficiency, High CRI, Binned and Mixed to Reach Uniform Light.

Lamp


LED Type: Built-in (Color Temperature Option – 3500K, 5000K)
CFL Type: GU24 CFL Bulb (Color Temperature Option – 2700K, 4000K)

Certification

UL/cUL, ETL/cETL Listed

Warranty

5 Years Warranty on Driver and LED Module



LED Type

Model	Input Voltage	Power	LED CT / CRI	Lumen (TYP)	Dimension (OD X H)	Finish
USL-DC82S-24W-30K	120V ~ 277V	24W	3000K / 80	1550	17.5" x 5.5"	Acrylic / Linen
USL-DC82S-24W-40K	120V ~ 277V	24W	4000K / 80	1640	17.5" x 5.5"	Acrylic / Linen
USL-DC82S-35W-30K	120V ~ 277V	35W	3000K / 80	2210	20.8" x 6.1"	Acrylic / Linen
USL-DC82S-35W-40K	120V ~ 277V	35W	4000K / 80	2250	20.8" x 6.1"	Acrylic / Linen