

EXTERIOR USL-ALIC

3-Arm Circular Post Light




Exterior


Wet Location


Dimmable


5 Year Warranty


DLC


ETL

OVERVIEW

This post light is ideal for use in areas such as pathways and parking lots. The body features an integrated heat sink for thermal management. It has 3 arms to create a balanced look.

FEATURES

- Type 4 distribution
- IP65
- Aluminum die-cast fixture
- Fits 2 3/8 or 3" tenons



ORDERING INFORMATION

EXAMPLE PN: USL-ALIC-50W-LV-40K-10V-D-3-0

USL-ALIC	POWER*	VOLTAGE	CCT*	DIMMING	FINISH	MOUNTING	PHOTOCELL
	50W 50W	LV 100-277V	30K 3000K	10V 0-10V	D BRONZE	2 2 3/8"	0 NONE
	75W 75W		40K 4000K		B BLACK	TENON	P PHOTOCELL
	100W 100W		50K 5000K		W WHITE	3 3" TENON	
	170W 170W		57K 5700K		G GRAY		

*Note: 100/170W only available in 5000K or 5700K

EXTERIOR USL-ALIC

3-Arm Circular Post Light



SPECIFICATIONS

MODEL	OPERATION VOLTAGE	OPERATING TEMPERATURE	RATED LIFESPAN	CCT	CRI	EFFICACY
USL-ALIC	100-277V AC	-22°F – 122°F -30°C – 50°C	50,000 HOURS	3000K, 4000K 5000K, 5700K	73+	98-114 lm/W

MODEL	POWER (W)	LUMENS (lm) at:				EFFICACY (lm/W)	MH REPLACEMENT
		3000K	4000K	5000K	5700K		
USL-ALIC-50W	50	5,497	5,497	5,497	5,685	110-114	100-150W
USL-ALIC-75W	75	8,147	8,241	8,335	8,429	109-112	150-200W
USL-ALIC-100W	100	NA	NA	9,807	9,964	98-100	300-400W
USL-ALIC-170W	170	NA	NA	17,218	17,465	101-103	400-600W

DIMENSIONS

MODEL	D DIAMETER	H HEIGHT
ALL MODELS	17.5 in 450 mm	25.5 in 650 mm

