

# INTERIOR USL-WA1D

## Linear Wraparound Fixture



### OVERVIEW

This linear fixture can be suspended or surface mounted on ceilings and walls. It is suitable in uses such as storage areas, utility areas, cove lighting, and task lighting.



### FEATURES

- 0-10V dimming
- Suspended or surface mount
- Isolated power supply
- Wider range of CCT options

### ORDERING INFORMATION

EXAMPLE PN: USL-WA1D-4-40W-30K-M-10V

USL-WA1D	SIZE / POWER	CCT	LENS	DIMMING
	<b>4-40W</b> 4FT, 40 WATTS	<b>30K</b> 2800-3100K	<b>C</b> CLEAR	<b>10V</b> 0-10V
		<b>40K</b> 3800-4250K	<b>M</b> MILKY	
		<b>50K</b> 4750-5300K		
		<b>60K</b> 5700K-6500K		

# INTERIOR USL-WA1D

## Linear Wraparound Fixture



### SPECIFICATIONS

MODEL	OPERATION VOLTAGE	OPERATING TEMPERATURE	RATED LIFESPAN	CCT	CRI	EFFICACY
USL-WA1D	100-277V	-4°F – 104°F -20°C – 40°C	50,000 HOURS	2800K-6500K	80+	102-123 lm/W

MODEL	POWER (W)	SPEC	LUMENS (lm) ±10%				EFFICACY (lm/W)
			3000K	4000K	5000K	6000K	
USL-WA1D-4-40W	40	CLEAR LENS	4,650	4,925	4,750	4,775	116-123
USL-WA1D-4-40W	40	MILKY LENS	4,075	4,475	4,225	4,250	102-112

### DIMENSIONS

MODEL	L LENGTH	W WIDTH	H HEIGHT
<b>4-40W</b>	47.2 in 1220 mm	56 in 152 mm	2.5 in 64 mm

