

INTERIOR USL-SB2C Round Downlight Panel



OVERVIEW

These LED round panels are an ideal replacement for commercial and residential downlighting applications. The round panel range is sized to be inserted directly into standard sized cut holes for down lights. The edge-lit design reduces glare.

FEATURES

- Low UGR
- Replaces 4-8" down lights
- Integrated heat sink
- IP20
- 4" and 8" Energy Star listed
- Slim profile for easier installation
- 120° beam angle



ORDERING INFORMATION

EXAMPLE PN: USL-SB2C-4R8W-LV-30K-10V

USL-SB2C	SIZE / POWER	VOLTAGE	CCT	DIMMING
4R8W	4" 8 WATTS CLASSIC	LV 100-277V	30K 3000K	0 NONE
4R9W	4" 9 WATTS ULTRA-SLIM	34V 347V	40K 4000K	10V 0-10V DIMMING
6R12W	6" 12 WATTS CLASSIC		50K 5000K	
6R16W	6" 16 WATTS ULTRA-SLIM			
8R15W	8" 15 WATTS CLASSIC			
8R18W	8" 18 WATTS ULTRA-SLIM			

Note: This product has been discontinued. Select models are available in stock.

INTERIOR USL-SB2C Round Downlight Panel



SPECIFICATIONS

MODEL	OPERATION VOLTAGE	OPERATING TEMPERATURE	RATED LIFESPAN	CCT	CRI	EFFICACY
	100-277V 347V	-40°F – 113°F -40°C – 45°C	50,000 HOURS	3000K, 4000K, 5000K	80+	80-102 lm/W

MODEL	SIZE (in)	POWER (W)	CCT	LUMENS (lm)	EFFICACY (lm/W)
USL-SB2C-4R8W-xx-30K	4	8	3000K	640	80
USL-SB2C-4R8W-xx-40K			4000K	650	81
USL-SB2C-4R8W-xx-50K			5000K	660	83
USL-SB2C-6R12W-xx-30K	6	12	3000K	1,180	98
USL-SB2C-6R12W-xx-40K			4000K	1,200	100
USL-SB2C-6R12W-xx-50K			5000K	1,220	102
USL-SB2C-8R15W-xx-30K	8	15	3000K	1,480	99
USL-SB2C-8R15W-xx-40K			4000K	1,500	100
USL-SB2C-8R15W-xx-50K			5000K	1,530	102

DIMENSIONS - LIGHT EMITTER

MODEL	D DIAMETER	W WIDTH	H HEIGHT	T THICKNESS
USL-SB2C-4R8W	4.5 in	1.1 in	2.1 in	0.51 in
	115 mm	28.5 mm		
USL-SB2C-6R12W	6.3 in	2.58 in		
	165 mm	66 mm		
USL-SB2C-8R15W	7.9 in	3 in		
	200 mm	77 mm		

DIMENSIONS - DRIVER

MODEL	A WIDTH	B HEIGHT	C LENGTH
ALL MODELS	2.7 in 65 mm	2.1 in 53.1 mm	8 in 203 mm

