


INTERIOR USL-UCBIL Under Cabinet Light



PROJECT		TYPE		DATE	
---------	--	------	--	------	--



OVERVIEW

This basic under cabinet light features a slim profile that requires minimal cabinet depth for mounting. It has an on/off switch for simple operation by the end-user.



FEATURES

- On/off switch
- 1-foot to 5 foot-models
- 3000K to 6500K
- Epistar 2835 LED
- Polycarbonate lens

ORDERING INFORMATION

EXAMPLE PN: USL-UCBIL-2-10W-40K-W

USL-UCBIL	SIZE / POWER	CCT	FINISH	DRIVER
1-6W	1 FOOT 6 WATTS	30K 3000K	W WHITE	LV 100-277V
2-10W	2 FEET 10 WATTS	40K 4000K	B BLACK	POE NO DRIVER (FOR POE)
3-15W	3 FEET 15 WATTS	50K 5000K	S SILVER	
4-20W	4 FEET 20 WATTS	65K 6500K		
5-25W	5 FEET 25 WATTS			
5-30W	5 FEET 30 WATTS			

INTERIOR USL-UCBIL Under Cabinet Light



SPECIFICATIONS

MODEL	OPERATION VOLTAGE	RATED LIFESPAN	CCT	CRI	EFFICACY
USL-UCBIL	100-277V	50,000 HOURS	3000K, 4000K, 5000K, 6500K	83+	105 lm/W

MODEL	POWER (W)	LUMENS (lm) ±10%	EFFICACY (lm/W)
USL-UCBIL-1-6W	6	630	105
USL-UCBIL-2-10W	10	1,050	105
USL-UCBIL-3-15W	15	1,575	105
USL-UCBIL-4-20W	20	2,100	105
USL-UCBIL-5-25W	25	2,625	105
USL-UCBIL-5-30W	30	3,150	105

POE OPERATING DETAILS

MODEL	CURRENT	VOLTAGE
USL-UCBIL-1-6W	130 mA	40-45V
USL-UCBIL-2-10W	240 mA	
USL-UCBIL-3-15W	310 mA	
USL-UCBIL-4-20W	430 mA	
USL-UCBIL-5-25W	510 mA	
USL-UCBIL-5-30W	600 mA	

DIMENSIONS

MODEL	L LENGTH	W WIDTH	H HEIGHT
USL-UCBIL-1-6W	12.4 in	2.5 in 63 mm	1.2 in 30 mm
	314 mm		
USL-UCBIL-2-10W	22.3 in		
	567 mm		
USL-UCBIL-3-15W	35.2 in		
	893 mm		
USL-UCBIL-4-20W	46.3 in		
	1177 mm		
USL-UCBIL-5-25W	58.4 in		
	1483 mm		
USL-UCBIL-5-30W	58.4 in		
	1483 mm		